


LED TV 32/43LT340C* 32/43LT340H*



🕀 : Depending on model / حسب الطراز






• Read Safety and Reference.

• For the power supply and power consumption, refer to the label attached to the product.

قراءة الأمان والمرجع.
 لمعرفة المزيد حول مصدر الإمداد بالطاقة المطلوب ومعايير استهلاك الطاقة، راجع الملصق الموجود على المنتج.


العربية






















































| | A | B | С | D | 8 | 6 | G |
|---|-----|-----|------|-----|------|--|----------|
| | | | (mm) | | | | (kg) |
| 32LT340CBTB 32LT340CBGB 32LT340HBGB | 739 | 472 | 168 | 441 | 84 | 4.90 | 4.85 |
| 43LT340C0TB 43LT340C0GB 43LT340H0GB | 977 | 615 | 187 | 575 | 80.8 | 8.1 | 8.0 |
| متطلبات الطاقة / Power requirement | | | | | | 5 ~ 240 V = 100-240 V 240 فولت ~ 50 / | |



OWNER'S MANUAL RS-232C

LED TV*

* LG LED TV applies LCD screen with LED backlights.

Please read this manual carefully before operating your set and retain it for future reference.

www.lg.com

IR CODES

• This feature is not available for all models.

| Code (Hexa) | Function | Note |
|----------------|------------------------|---|
| 08 | (POWER) | Remote control Button (Power On/Off) |
| 95 | ۯENERGY SAVING | Remote control Button |
| 30 | O AV MODE | Remote control Button |
| OB | - INPUT (INPUT) | Remote control Button |
| FO | TV/RAD 📺/🖾 | Remote control Button |
| 10-19 | Number Key 0-9 | Remote control Button |
| 53 | LIST | Remote control Button |
| 1A | Q.VIEW | Remote control Button |
| 02 | +⊿ | Remote control Button |
| 03 | ⊿- | Remote control Button |
| 1E | FAV | Remote control Button |
| 79 | RATIO ⊕RATIO | Remote control Button |
| 09 | MUTE 吋 📌 (MUTE) | Remote control Button |
| 00 | ∧P }PAGE ∧PAGE | Remote control Button |
| 01 | P∨∕ PAGE↓ PAGE∨∕ | Remote control Button |
| AB | GUIDE | Remote control Button |
| 0C | PORTAL | Remote control Button |
| AA | () INFO INFO () | Remote control Button |
| 40 | | Remote control Button |
| 41 | Ť | Remote control Button |

| Code (Hexa) | Function | Note |
|----------------|-------------------------|-----------------------|
| 07 | | Remote control Button |
| 06 | > | Remote control Button |
| 44 | 0K 🖲 © 0K | Remote control Button |
| 43 | SETTINGS | Remote control Button |
| 28 | ⇒(BACK) BACK | Remote control Button |
| 5B | EXIT [] EXIT | Remote control Button |
| 72 | • | Remote control Button |
| 71 | •• | Remote control Button |
| 63 | | Remote control Button |
| 61 | | Remote control Button |
| 20 | TEXT | Remote control Button |
| 21 | T.OPT(T.Option) | Remote control Button |
| 39 | SUBTITLE | Remote control Button |
| B1 | | Remote control Button |
| BO | • | Remote control Button |
| BA | I | Remote control Button |
| 8F | * | Remote control Button |
| 8E | ▶ | Remote control Button |
| 7E | Smplink | Remote control Button |
| 45 | Q.MENU | Remote control Button |
| 91 | AD | Remote control Button |
| E8 | ALARM | Remote control Button |
| 7C | (HOME) | Remote control Button |
| BD | ●REC/* | Remote control Button |

EXTERNAL CONTROL DEVICE SETUP


RS-232C Setup

• Image shown may differ from your TV.

Connect the RS-232C (serial port) input jack to an external control device (such as a computer or an A/V control system) to control the product's functions externally.

Connect the serial port of the control device to the RS-232C jack on the product back panel.

• RS-232C connection cables are not supplied with the product.




(Depending on model)


Phone jack Type

(Depending on model)

- You need to purchase the phone-jack to RS-232C cable required for the connection between the PC and the TV, which is specified in the manual.
- * For other models, connect to the USB port.
- * The connection interface may differ from your TV.




Type of Connector : D-Sub 9-Pin Male




| No. | Pin name |
|-----|---|
| 1 | 3.5 V |
| 2 | RXD (Receive data) |
| 3 | TXD (Transmit data) |
| 4 | IR OUT from TV |
| 5 | GND |
| 6 | No Connection |
| 7 | No Connection (5 V available in some models) |
| 8 | No Connection |
| 9 | No Connection (12 V available in some models) |

RS-232C Configurations

ENGLISH





| | PC | | TV | |
|-----|---------|----|---------|-----|
| RXD | 2 | •• | 3 | TXD |
| TXD | 3 | •• | 2 | RXD |
| GND | 5 | •• | 5 | GND |
| DTR | 4 | | 6 | DSR |
| DSR | 6 | | 4 | DTR |
| RTS | 7 | | 8 | RTS |
| CTS | 8 | | 7 | CTS |
| | D-Sub 9 | | D-Sub 9 | |

Communication Parameters

- Baud rate: 9,600 bps (UART)
- Data length: 8 bits
- Parity: None
- Stop bit: 1 bit
- Communication code: ASCII code
- Use a crossed (reverse) cable.

Command Reference List

(Depending on model)

| | Command1 | Command2 | Data (Hexadecimal) |
|-----------------------------------|----------|----------|-----------------------|
| 1 Power | k | а | 00 to 01 |
| 2 [Aspect Ratio] | k | с | (See p. 5) |
| 3 Screen Mute | k | d | (See p. 6) |
| 4 Volume Mute | k | e | 00 to 01 |
| 5 Volume Control | k | f | 00 to 64 |
| 6 [Contrast] | k | g | 00 to 64 |
| 7 [Brightness] | k | h | 00 to 64 |
| 8 [Colour] | k | i | 00 to 64 |
| 9 [Tint] | k | j | 00 to 64 |
| 10 [Sharpness] | k | k | 00 to 32 |
| 11 OSD Select | k | I | 00 to 01 |
| 12 Remote Control Lock Mode | k | m | 00 to 01 |
| 13 [Balance] | k | t | 00 to 64 |
| 14 [Colour Temperature] | х | u | 00 to 64 |
| 15 [Energy Saving] | j | q | (See p. 8) |
| 16 [Auto Configuration] | j | u | 01 |
| 17 [Equalizer] | j | v | (See p. 8) |
| 18 Tune Command | m | а | (See p. 9) |
| 19 Programme [Skip/Add] | m | b | 00 to 01 |
| 20 Key | m | c | (See p. 9) |
| 21 Control [Backlight] | m | g | 00 to 64 |
| 22 [Input] select | х | b | (See p. 10) |

• During USB operations such as DivX or EMF, all commands except Power(ka) and Key(mc) are not executed and treated as NG.

Transmission / Receiving Protocol

(Depending on Model)

Transmission

(Command1)(Command2)()([Set ID])()([Data])(Cr)

(Command1) : First command to control the TV. (j, k, m or x) (Command2) : Second command to control the TV.

([Set ID]) : You can adjust the set ID to choose desired monitor ID number in option menu. Adjustment range is 1 to 99. When selecting Set ID'0', every connected set is controlled. Set ID is indicated as decimal (1 to 99) on menu and as Hexa decimal (0 x 0 to 0 x 63) on transmission/receiving protocol.

([Data]) : To transmit command data. Transmit 'FF' data to read status of command.

(Cr) : Carriage Return

ASCII code '0 x 0D'

(): ASCII code 'space (0 x 20)'

OK Acknowledgement

(Command2)()([Set ID])()(OK)([Data])(x)

* The set transmits ACK (acknowledgement) based on this format when receiving normal data. At this time, if the data is data read mode, it indicates present status data. If the data is data write mode, it returns the data of the PC computer.

Error Acknowledgement

(Command2)()([Set ID])()(NG)([Data])(x)

* The set transmits ACK (acknowledgement) based on this format when receiving abnormal data from non-viable functions or communication errors.

[Data] 00 : Illegal Code

1 Power (Command: k a)

► To control Power On/Off of the set.

Transmission

(k)(a)()([Set ID])()([Data])(Cr)

[Data] 00 : [Off] [Data] 01 : [On]

Ack

(a)()([Set ID])()(OK/NG)([Data])(x)

► To Show TV is Power On/Off.

Transmission

(k)(a)()([Set ID])()(FF)(Cr)

Ack

(a)()([Set ID])()(OK/NG)([Data])(x)

- * Similarly, if other functions transmit '0 x FF' data based on this format, Acknowledgement data feed back presents status about each function.
- * OK Ack., Error Ack. and other message may display on the screen when TV is power On.
- 2 [Aspect Ratio] (Command: k c) (Main Picture Size)
- To adjust the screen format. (Main picture format) You can also adjust the screen format using the picture settings.

Transmission

(k)(c)()([Set ID])()([Data])(Cr)

[Data] 01 : [4:3] (Normal screen - [Just Scan] Off)

- [Data] 02 : [16:9] (Wide screen [Just Scan] Off)
- [Data] 06 : [Original] ([Just Scan] Off)

[Data] 09 : [Just Scan]

* Please make sure that the model doesn't support both Vertical Zoom and All-Direction Zoom mode.

Ack

(c)()([Set ID])()(OK/NG)([Data])(x)

- * Using the PC input, you select either 16:9 or 4:3 screen aspect ratio.
- * In DTV/HDMI (1080i 50 Hz / 60 Hz, 720p 50Hz / 60 Hz, 1080p 24 Hz / 30 Hz / 50 Hz / 60 Hz), Component (720p, 1080i, 1080p) mode, [Just Scan] is available.
- * Full Wide is supported only for Digital, Analogue, AV.

3 Screen Mute (Command: k d)

To select screen mute on/off.

Transmission

(k)(d)()([Set ID])()([Data])(Cr)

[Data] 00 : Screen mute off (Picture on) / Video mute off [Data] 01 : Screen mute on (Picture off) [Data] 10 : Video mute on

Ack

(d)()([Set ID])()(OK/NG)([Data])(x)

- * In case of video mute on only, TV will display On Screen Display (OSD). But, in case of Screen mute on, TV will not display OSD.
- 4 Volume Mute (Command: k e)
- To control volume mute on/off. You can also adjust mute using the mute button on remote control.

Transmission

(k)(e)()([Set ID])()([Data])(Cr)

[Data] 00 : Volume mute on (Volume off)

[Data] 01 : Volume mute off (Volume on)

Ack

(e)()([Set ID])()(OK/NG)([Data])(x)

5 Volume Control (Command: k f)

To adjust volume. You can also adjust volume with the volume buttons on remote control.

Transmission

(k)(f)()([Set ID])()([Data])(Cr)

[Data] Min : 00 to Max : 64

* Refer to "Real data mapping".

Ack

(f)()([Set ID])()(OK/NG)([Data])(x)

6 [Contrast] (Command: kg)

To adjust screen contrast.
 You can also adjust contrast in the picture settings.

Transmission

(k)(g)()([Set ID])()([Data])(Cr)

Data Min: 00 to Max: 64

* Refer to "Real data mapping".

Ack

(g)()([Set ID])()(OK/NG)([Data])(x)

- 7 [Brightness] (Command: k h)
- To adjust screen brightness.
 You can also adjust brightness in the picture settings.

Transmission

(k)(h)()([Set ID])()([Data])(Cr)

Data Min: 00 to Max: 64

* Refer to "Real data mapping".

Ack

(h)()([Set ID])()(OK/NG)([Data])(x)

- 8 [Colour] (Command: k i)
- To adjust the screen colour. You can also adjust colour in the picture settings.

Transmission

(k)(i)()([Set ID])()([Data])(Cr)

[Data] Min : 00 to Max : 64

* Refer to "Real data mapping".

Ack

(i)()([Set ID])()(OK/NG)([Data])(x)

- 9 [Tint] (Command: k j)
- To adjust the screen tint. You can also adjust tint in the picture settings.

Transmission

(k)(j)()([Set ID])()([Data])(Cr)

[Data] Red : 00 to Green : 64

* Refer to "Real data mapping".

Ack

(j)()([Set ID])()(OK/NG)([Data])(x)

10 [Sharpness] (Command: k k)

 To adjust the screen sharpness. You can also adjust sharpness in the picture settings.

Transmission

(k)(k)()([Set ID])()([Data])(Cr)

[Data] Min : 00 to Max : 32

* Refer to "Real data mapping".

Ack

(k)()([Set ID])()(OK/NG)([Data])(x)

11 OSD Select (Command: k l)

 To select OSD (On Screen Display) on/off when controlling remotely. Transmission

(k)(l)()([Set ID])()([Data])(Cr)

[Data] 00 : [Off] [Data] 01 : [On]

Ack

(I)()([Set ID])()(OK/NG)([Data])(x)

12 Remote Control Lock Mode (Command: km)

► To lock the front panel controls on the monitor and remote control.

Transmission

(k)(m)()([Set ID])()([Data])(Cr)

[Data] 00 : [Off] [Data] 01 : [On] Ack

(m)()([Set ID])()(OK/NG)([Data])(x)

- * If you are not using the remote control, use this mode. When main power is on/off, external control lock is released.
- * In the standby mode, if key lock is on, TV will not turn on by power on key of IR & Local Key.

13 [Balance] (Command: k t)

 To adjust balance. You can also adjust balance in the audio settings.

Transmission

(k)(t)()([Set ID])()([Data])(Cr)

[Data] L : 00 to R : 64

* Refer to "Real data mapping".

Ack

(t)()([Set ID])()(OK/NG)([Data])(x)

14 [Colour Temperature] (Command: x u)

 To adjust Colour Temperature. You can also adjust Colour Temperature in the picture settings.

Transmission

(x)(u)()([Set ID])()([Data])(Cr)

[Data] Warm: 00 to Cool:64

* Refer to "Real data mapping".

Ack

(u)()([Set ID])()(OK/NG)([Data])(x)

15 [Energy Saving] (Command: j q)

► To reduce the power consumption of the TV. You can also adjust Energy Saving in picture settings.

Transmission

(j)(q)()([Set ID])()([Data])(Cr)

| Po | Power Saving Function | | | | Level | | | | Description |
|----|--------------------------|---|---|--------------|-------|---|---|---|--------------|
| 7 | 6 | 5 | 4 | | 3 | 2 | 1 | 0 | |
| 0 | 0 | 0 | 0 | Low Power | 0 | 0 | 0 | 0 | [0ff] |
| 0 | 0 | 0 | 0 | Low Power | 0 | 0 | 0 | 1 | [Minimum] |
| 0 | 0 | 0 | 0 | Low Power | 0 | 0 | 1 | 0 | [Medium] |
| 0 | 0 | 0 | 0 | Low Power | 0 | 0 | 1 | 1 | [Maximum] |
| 0 | 0 | 0 | 0 | Low Power | 0 | 1 | 0 | 1 | [Screen Off] |
| 0 | 0 | 0 | 0 | Low Power | 0 | 1 | 0 | 0 | [Auto] |

► [Auto] is available in TV that supports 'Intelligent Sensor'.

Ack

(q)()([Set ID])()(OK/NG)([Data])(x)

16 [Auto Configuration] (Command: j u) (Only RGB support model)

► To adjust picture position and minimize image shaking automatically. It works only in RGB (PC) mode.

Transmission

(j)(u)()([Set ID])()([Data])(Cr)

[Data] 01 : To set

Ack


(u)()([Set ID])()(OK/NG)([Data])(x)

17 [Equalizer] (Command : j v)

► To adjust equalizer.

Transmission

(j)(v)()([Set ID])()([Data])(Cr)



| 7 | 6 | 5 | Frequency | 4 | 3 | 2 | 1 | 0 | Step |
|---|---|---|-----------|---|---|---|---|---|--------------|
| 0 | 0 | 0 | 1st Band | 0 | 0 | 0 | 0 | 0 | 0 (decimal) |
| 0 | 0 | 1 | 2nd Band | 0 | 0 | 0 | 0 | 1 | 1 (decimal) |
| 0 | 1 | 0 | 3rd Band | | | | | | |
| 0 | 1 | 1 | 4th Band | 1 | 0 | 0 | 1 | 1 | 19 (decimal) |
| 1 | 0 | 0 | 5th Band | 1 | 0 | 1 | 0 | 0 | 20 (decimal) |

Ack

(v)()([Set ID])()(OK/NG)([Data])(x)

18 Tune Command (Command: m a)

Select channel to following physical number.

Transmission

(m)(a)()([Set ID])()([Data] 00)()([Data] 01)()([Data] 02)(Cr)

[Data] 00 : High channel data [Data] 01 : Low channel data ex. No. 47 \rightarrow 00 2F (2FH) No. $394 \rightarrow 01.8A (18AH)$. DTV No. 0 \rightarrow Don't care [Data] 02 : (Antenna) 0 x 00 : Analogue Main 0 x 10 : DTV Main 0 x 20 : Radio (Cable) 0 x 80 : Analogue Main 0 x 90 : DTV Main 0 x A0 : Radio (Satellite) (Depending on model) 0 x 40 : DTV Main 0 x 50 : Radio Main Channel data range Min: 00 Max: 270F (0 to 9999) Ack (a)()([Set ID])()(OK/NG)([Data])(x)

19 Programme [Skip/Add] (Command: m b)

To set skip status for the current Programme.

Transmission

(m)(b)()([Set ID])()([Data])(Cr)

[Data] 00 : [Skip] [Data] 01 : [Add] Ack (b)()([Set ID])()(OK/NG)([Data])(x)

20 Key (Command: m c) ► To send IR remote key code. Transmission (m)(c)(([Set ID])()([Data])(Cr) [Data] IR CODES Ack (c)()([Set ID])()(OK/NG)([Data])(x) 21 Control [Backlight] (Command: m g)

To control the backlight.

Transmission

(m)(g)()([Set ID])()([Data])(Cr)

[Data] Min : 00 to Max : 64

Ack


(g)()([Set ID])()(OK/NG)([Data])(x)

- 22 [Input] select (Command: x b) (Main Picture Input)
- ► To select input source for main picture.

Transmission

(x)(b)()([Set ID])()([Data])(Cr)

[Data] Structure



| | Externa | al Input | Data | | |
|---|---------|----------|------|-------------|--|
| 0 | 0 | 0 | 0 | [DTV] | |
| 0 | 0 | 0 | 1 | [Analogue] | |
| 0 | 0 | 1 | 0 | [AV] | |
| 0 | 1 | 0 | 0 | [Component] | |
| 0 | 1 | 1 | 0 | [RGB] | |
| 0 | 1 | 1 | 1 | | |
| 1 | 0 | 0 | 0 | [LIDMI] | |
| 1 | 0 | 0 | 1 | [HDMI] | |
| 1 | 0 | 1 | 0 | | |

| | Input M | lumber | Data | |
|---|---------|--------|------|--------|
| 0 | 0 | 0 | 0 | Input1 |
| 0 | 0 | 0 | 1 | Input2 |
| 0 | 0 | 1 | 0 | Input3 |
| 0 | 0 | 1 | 1 | Input4 |

Ack

(b)()([Set ID])()(OK/NG)([Data])(x)

| * Real dat | ta mapping |
|------------|-----------------------|
| 00 : | Step 0 |
| : | |
| A : | Step 10 ([Set ID] 10) |
| : | |
| F: | Step 15 ([Set ID] 15) |
| 10: | Step 16 ([Set ID] 16) |
| : | |
| 64: | Step 100 |
| : | |
| 6E : | Step 110 |
| : | |
| 73: | Step 115 |
| 74: | Step 116 |
| : | |
| CF: | Step 199 |
| : | |
| FE: | Step 254 |
| FF: | Step 255 |



The model and serial number of the product are located on the back and on one side of the product. Record them below in case you ever need service.

| MODEL | |
|-----------|--|
| SERIAL NO | |



OWNER'S MANUAL

Safety and Reference



* LG LED TV applies LCD screen with LED backlights.

Please read this manual carefully before operating your set and retain it for future reference.



www.lg.com

Warning! Safety Instructions



CAUTION : TO REDUCE THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK). NO USER-SERVICEABLE PARTS INSIDE. REFER TO QUALIFIED SERVICE PERSONNEL.

This symbol is intended to alert the user to the presence of uninsulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.

This symbol is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

WARNING : TO REDUCE THE RISK OF FIRE AND ELECTRIC SHOCK, DO NOT EXPOSE THIS PRODUCT TO RAIN OR MOISTURE.

TO PREVENT THE SPREAD OF FIRE, KEEP CANDLES OR OTHER ITEMS WITH OPEN FLAMES AWAY FROM THIS PRODUCT AT ALL TIMES.

- Do not place the TV and/or remote control in the following environments:
 - Keep the product away from direct sunlight.
 - An area with high humidity such as a bathroom.
 - Near any heat source such as stoves and other devices that produce heat.
 - Near kitchen counters or humidifiers where they can easily be exposed to steam or oil.
 - An area exposed to rain or wind.
 - Do not expose to dripping or splashing and do not place objects filled with liquids, such as vases, cups, etc. on or over the apparatus (e.g., on shelves above the unit).
 - Near flammable objects such as gasoline or candles, or expose the TV to direct air conditioning.
 - Do not install in excessively dusty places.

Otherwise, this may result in fire, electric shock, combustion/ explosion, malfunction or product deformation.

- Ventilation
 - Install your TV where there is proper ventilation. Do not install in a confined space such as a bookcase.
 - Do not install the product on a carpet or cushion.
 - Do not block or cover the product with cloth or other materials while unit is plugged in.
- Take care not to touch the ventilation openings. When watching the TV for a long period, the ventilation openings may become hot.
- Protect the power cord from physical or mechanical abuse, such as being twisted, kinked, pinched, closed in a door, or walked upon. Pay particular attention to plugs, wall outlets, and the point where the cord exits the device.
- Do not move the TV whilst the Power cord is plugged in.
- Do not use a damaged or loosely fitting power cord.
- Be sure to grasp the plug when unplugging the power cord. Do not pull on the power cord to unplug the TV.
- Do not connect too many devices to the same AC power outlet as this could result in fire or electric shock.
- Disconnecting the Device from the Main Power
 - The power plug is the disconnecting device. In case of an emergency, the power plug must remain readily accessible.
- Do not let your children climb or cling onto the TV. Otherwise, the TV may fall over, which may cause serious injury.
- Outdoor Antenna Grounding (Can differ by country):
 - If an outdoor antenna is installed, follow the precautions below.
 An outdoor antenna system should not be located in the vicinity of overhead power lines or other electric light or power circuits, or where it can come in contact with such power lines or circuits as death or serious injury can occur.

Be sure the antenna system is grounded to provide some protection against voltage surges and built-up static charges. Section 810 of the National Electrical Code (NEC) in the U.S.A. provides information with respect to proper grounding of the mast and supporting structure, grounding of the lead-in wire to an antenna discharge unit, size of grounding conductors, location of antenna discharge unit, connection to grounding electrodes and requirements for the grounding electrode.

Antenna grounding according to the National Electrical Code, ANSI/ NFPA 70

- Grounding (Except for devices which are not grounded.)
 - TV with a three-prong grounded AC plug must be connected to a three-prong grounded AC outlet. Ensure that you connect the earth ground wire to prevent possible electric shock.
- Never touch this apparatus or antenna during a lightning storm. You may be electrocuted.
- Make sure the power cord is connected securely to the TV and wall socket if not secured damage to the Plug and socket may occur and in extreme cases a fire may break out.
- Do not insert metallic or inflammable objects into the product. If a foreign object is dropped into the product, unplug the power cord and contact the customer service.
- Do not touch the end of the power cord while it is plugged in. You may be electrocuted.
- If any of the following occur, unplug the product immediately and contact your local customer service.
 - The product has been damaged.
 - If water or another substance enters the product (like an AC adapter, power cord, or TV).
 - If you smell smoke or other odors coming from the TV.
 - When lightning storms or when unused for long periods of time. Even if the TV is turned off by the remote control or power button, AC power source is still connected to the unit if it is not unplugged.
- Do not use high voltage electrical equipment near the TV (e.g., a bug zapper). This may result in product malfunction.
- Do not attempt to modify this product in any way without written authorization from LG Electronics. Accidental fire or electric shock can occur. Contact your local customer service for service or repair. Unauthorized modification could void the user's authority to operate this product.
- Use only an authorized attachments / accessories approved by LG Electronics. Otherwise, this may result in fire, electric shock, malfunction, or product damage.
- Never disassemble the AC adapter or power cord. This may result in fire or electric shock.
- Handle the adapter carefully to avoid dropping or striking it. An impact could damage the adapter.
- To reduce the risk of fire or electrical shock, do not touch the TV with wet hands. If the power cord prongs are wet or covered with dust, dry the power plug completely or wipe dust off.

Batteries

- Store the accessories (battery, etc.) in a safe location out of the reach of children.
- Do not short circuit, disassemble, or allow the batteries to overheat. Do not dispose of batteries in a fire. Batteries should not be exposed to excessive heat.

Moving

- When moving, make sure the product is turned off, unplugged, and all cables have been removed. It may take 2 or more people to carry larger TVs. Do not press or put stress on the front panel of the TV.
 Otherwise, this may result in product damage, fire hazard or injury.
- Keep the packing anti-moisture material or vinyl packing out of the reach of children.
- Do not allow an impact shock, any objects to fall into the product, and do not drop anything onto the screen.
- Do not press strongly upon the panel with a hand or a sharp object such as a nail, pencil, or pen, or make a scratch on it. It may cause damage to screen.

Cleaning

 When cleaning, unplug the power cord and wipe gently with a soft/dry cloth. Do not spray water or other liquids directly on the TV. Do not clean your TV with chemicals including glass cleaner, any type of air freshener, insecticide, lubricants, wax (car, industrial), abrasive, thinner, benzene, alcohol etc., which can damage the product and/or its panel. Otherwise, this may result in electric shock or product damage.

Preparing

- If the TV is turned on for the first time after it was shipped from the factory, initialization of the TV may take a few minutes.
- Image shown may differ from your TV.
- Your TV's OSD (On Screen Display) may differ slightly from that shown in this manual.
- The available menus and options may differ from the input source or product model that you are using.
- New features may be added to this TV in the future.
- The device must be easily accessed to a location outlet near the access. Some devices are not made by turning on / off button, turning off the device and unplugging the power cord.
- The items supplied with your product may vary depending on the model.
- Product specifications or contents of this manual may be changed without prior notice due to upgrade of product functions.
- For an optimal connection, HDMI cables and USB devices should have bezels less than 10 mm thick and 18 mm width. Use an extension cable that supports USB 2.0 if the USB cable or USB memory stick does not fit into your TV's USB port.



* A ≦ 10 mm * B ≦ 18 mm

- Use a certified cable with the HDMI logo attached.
- If you do not use a certified HDMI cable, the screen may not display or a connection error may occur. (Recommended HDMI Cable Types)
 - Ultra High-Speed HDMI®/™ Cable (3 m or less)


Separate Purchase

Separate purchase items can be changed or modified for quality improvement without any notification. Contact your dealer to buy these items. These devices only work with certain models.

The model name or design may be changed depending on the upgrade of product functions, manufacturer's circumstances or policies.

Wall Mounting Bracket

Make sure to use screws and wall mount bracket that meet the VESA standard. Standard dimensions for the wall mount kits are described in the following table.



| Model | 32/43LT34* | 49LT34* |
|--------------------|-------------------|-------------------|
| VESA (A x B) (mm) | 200 x 200 | 300 x 300 |
| Standard screw | M6 | M6 |
| Number of screws | 4 | 4 |
| Wall mount bracket | LSW240B MSW240 | OLW480B MSW240 |


Lifting and moving the TV

Please note the following advice to prevent the TV from being scratched or damaged and for safe transportation regardless of its type and size.

- It is recommended to move the TV in the box or packing material that the TV originally came in.
- Before moving or lifting the TV, disconnect the power cord and all cables.
- When holding the TV, the screen should face away from you to avoid damage.



• Hold the top and bottom of the TV frame firmly. Make sure not to hold the transparent part, speaker, or speaker grill area.



- When transporting a large TV, there should be at least 2 people.
- When transporting the TV by hand, hold the TV as shown in the following illustration.




- When transporting the TV, do not expose the TV to jolts or excessive vibration.
- When transporting the TV, keep the TV upright, never turn the TV on its side or tilt towards the left or right.
- Do not apply excessive pressure to cause flexing / bending of frame chassis as it may damage the screen.
- When handling the TV, be careful not to damage the protruding buttons.



- Avoid touching the screen at all times, as this may result in damage to the screen.
- Do not move the TV by holding the cable holders, as the cable holders may break, and injuries and damage to the TV may occur.
- When attaching the stand to the TV set, place the screen facing down on a cushioned table or flat surface to protect the screen from scratches.

Mounting on a Table

- 1 Lift and tilt the TV into its upright position on a table.
 - Leave a 10 cm (minimum) space from the wall for proper ventilation.




- 2 Connect the power cord to a wall outlet.
 - Do not apply foreign substances (oils, lubricants, etc.) to the screw parts when assembling the product. (Doing so may damage the product.)
 - If you install the TV on a stand, you need to take actions to prevent the product from overturning. Otherwise, the product may fall over, which may cause injury.
 - Do not use any unapproved items to ensure the safety and product life span.
 - Any damage or injuries caused by using unapproved items are not covered by the manufacturer's warranty.
 - Make sure that the screws are inserted correctly and fastened securely. (If they are not fastened securely enough, the TV may tilt forward after being installed.) Do not use too much force and over tighten the screws; otherwise screw may be damaged and not tighten correctly.
 - If a television is not positioned in a sufficiently stable location, it can be potentially hazardous due to falling. Many injuries, particularly to children, can be avoided by taking simple precautions such as:
 - Using cabinets or stands recommended by the manufacturer of the television.
 - Only using furniture that can safely support the television.
 - Ensuring the television is not overhanging the edge of the supporting furniture.
 - Not placing the television on tall furniture (for example, cupboards or bookcases) without anchoring both the furniture and the television to a suitable support.
 - Not standing the televisions on cloth or other materials placed between the television and supporting furniture.
 - Educating children about the dangers of climbing on furniture to reach the television or its controls.

Using the Kensington security system


The Kensington security system connector is located at the rear of the TV. For more information of installation and using, refer to the manual provided with the Kensington security system or visit

http://www.kensington.com. Connect the Kensington security system cable between the TV and a table.



(Depending on model)

Securing the TV to a Wall




(Depending on model)

- 1 Insert and tighten the eye-bolts, or TV brackets and bolts on the back of the TV.
 - If there are bolts inserted at the eye-bolts position, remove the bolts first.
- 2 Mount the wall brackets with the bolts to the wall. Match the location of the wall bracket and the eye-bolts on the rear of the TV.
- 3 Connect the eye-bolts and wall brackets tightly with a sturdy rope. Make sure to keep the rope horizontal with the flat surface.
- Use a platform or cabinet that is strong and large enough to support the TV securely.
- Brackets, bolts and ropes are not provided. You can obtain additional accessories from your local dealer.

Mounting to the Wall

Attach an optional wall mount bracket at the rear of the TV carefully and install the wall mount bracket on a solid wall perpendicular to the floor. When you attach the TV to other building materials, please contact qualified personnel. LG recommends that wall mounting be performed by a qualified professional installer. We recommend the use of LG's wall mount bracket. LG's wall mount bracket is easy to move with cables connected. When you do not use LG's wall mount bracket, please use a wall mount bracket where the device is adequately secured to the wall with enough space to allow connectivity to external devices. It is advised to connect all the cables before installing fixed wall mounts.






• Remove the stand before installing the TV on a wall mount by performing the stand attachment in reverse.

- For more information of screws and wall mount bracket, refer to the Separate purchase.
- If you intend to mount the product to a wall, attach VESA standard mounting interface (optional parts) to the back of the product. When you install the set to use the wall mounting bracket (optional parts), fix it carefully so as not to drop.
- When mounting a TV on the wall, make sure not to install the TV by hanging the power and signal cables on the back of the TV.
- Do not install this product on a wall if it could be exposed to oil or oil mist. This may damage the product and cause it to fall.

ENGLISH

 When installing the wall mounting bracket, it is recommended to cover the stand hole using tape, in order to prevent the influx of dust and insects. (Depending on model)



Connections

Connect various external devices to the TV and switch input modes to select an external device. For more information of external device's connection, refer to the manual provided with each device.

Antenna/Cable

Connect the TV to a wall antenna socket with an RF cable (75 Ω).

- Use a signal splitter to use more than 2 TVs.
- If the image quality is poor, install a signal amplifier properly to improve the image quality.
- If the image quality is poor with an antenna connected, try to realign the antenna in the correct direction.
- An antenna cable and converter are not supplied.

Satellite dish

Connect the TV to a satellite dish to a satellite socket with a satellite RF cable (75 Ω). (Depending on model)

CI module

View the encrypted (pay) services in digital TV mode. (Depending on model)

- Check if the CI module is inserted into the PCMCIA card slot in the right direction. If the module is not inserted properly, this can cause damage to the TV and the PCMCIA card slot.
- If the TV does not display any video and audio when CI+ CAM is connected, please contact to the Terrestrial/Cable/Satellite Service Operator.

Other connections

Connect your TV to external devices. For the best picture and audio quality, connect the external device and the TV with the HDMI cable. Some separate cable is not provided.

HDMI

 Supported HDMI Audio format (Depending on model): DTS (44.1 kHz / 48 kHz), Dolby Digital / Dolby Digital Plus (32 kHz / 44.1 kHz / 48 kHz), PCM (32 kHz / 44.1 kHz / 48 kHz / 96 kHz / 192 kHz)

USB

It is recommended that you use an external USB HDD with a rated voltage of 5 V of less and a rated current of 500 mA or less.


ENGLISH

External Devices

Available external devices are: Blu-ray player, HD receivers, DVD players, VCRs, audio systems, USB storage devices, PC, gaming devices, and other external devices.

- The external device connection may differ from the model.
- Connect external devices to the TV regardless of the order of the TV port.
- Refer to the external equipment's manual for operating instructions.
- If you connect a gaming device to the TV, use the cable supplied with the gaming device.
- In PC mode, there may be noise associated with the resolution, vertical pattern, contrast or brightness. If noise is present, change the PC output to another resolution, change the refresh rate to another rate or adjust the brightness and contrast on the PICTURE menu until the picture is clear.
- In PC mode, some resolution settings may not work properly depending on the graphics card.
- When connecting via a wired LAN, it is recommended to use a CAT 7 cable. (Only when **LAN** port is provided.)

External Speakers





• Use only with the 3 Pole 3.5 mm Stereo Jack.

Do not connect your headphones or earphones to the port for connecting an external speaker.

Network


Using Button

(Depending on model)

Wired network connection


This TV can be connected to a Pro:Centric server via the **LAN** port. After making the physical connection, the TV needs to be set up for network communication.

Connect the LAN port of the Modem or Router from Pro:Centric server to the LAN port on the TV.



Connect the LAN port of the Modem or Router to the LAN port on the TV.

- Do not connect a modular phone cable to the LAN port.
- Since there are various connection methods, please follow the specifications of your telecommunication carrier or internet service provider.





Basic functions

Power On (Press) Power Off¹ (Press and Hold) Menu Control (Press²) Menu Selection (Press and Hold³)

- 1 All running apps will close.
- **2** You can access and adjust the menu by pressing the button when TV is on.
- **3** You can use the function when you access menu control.

Adjusting the menu

When the TV is turned on, press the **b** button one time. You can adjust the Menu items using the button.

| ወ | Turns the power off. |
|--------|---------------------------------------|
| ٩ | Changes the input source. |
| ^ ~ | Scrolls through the saved programmes. |
| + | Adjusts the volume level. |

ENGLISH

Using Remote Control

The descriptions in this manual are based on the buttons on the remote control. Please read this manual carefully and use the TV correctly.

To replace batteries, open the battery cover, replace batteries (1.5 V AAA) matching the \bigoplus and \bigoplus ends to the label inside the compartment, and close the battery cover. To remove the batteries, perform the installation actions in reverse.

Make sure to point the remote control toward the remote control sensor on the TV.

(Depending on model)



(Some buttons and services may not be provided depending on models or regions.)

* To use the button, press and hold for more than 3 seconds.

() (POWER) Turns the TV on or off. TV/RAD () Selects Radio, TV and DTV programme. SUBTITLE Recalls your preferred subtitle in digital mode. AD Audio descriptions function will be enabled. • RATIO Resizes an image. (INPUT) Changes the input source. Number buttons Enters numbers. LIST Accesses the saved programmes list. Q.VIEW Returns to the previously viewed programme. + — Adjusts the volume level. FAV Accesses your favourite programme list. **GUIDE** Shows programme guide. **MUTE)** Mutes all sounds. ***** (MUTE) Accesses the [Accessibility] menu. $\land P \lor$ Scrolls through the saved programmes. ∧ PAGE ∨ Moves to the previous or next screen.

Teletext buttons (TEXT, T.OPT) These buttons are used for teletext.

(HOME) Accesses the Home menu.

CALC (SETTINGS) Accesses the Settings menu.

Q.MENU Accesses the Quick menus.

Navigation buttons (up/down/left/right) Scrolls through menus or options.

OK Selects menus or options and confirms your input.

BACK Returns to the previous level.

EXIT Clears on-screen displays and returns to TV viewing.

DINFO Views the information of the current programme and screen.

• REC/* This function is not supported.

Control buttons (\blacksquare , \blacktriangleright , \blacksquare , \bigstar) Controls media contents.

• • • • These access special functions in some menus.



(Some buttons and services may not be provided depending on models or regions.)

* To use the button, press and hold for more than 3 seconds.

(POWER) Turns the TV on or off.

€ **ENERGY SAVING** Adjusts the brightness of the screen to reduce energy consumption.

O AV MODE Selects an AV mode.

- INPUT Changes the input source.

TV/RAD ()/ Selects Radio, TV and DTV programme.

Number buttons Enters numbers.

LIST Accesses the saved programme list.

Q.VIEW Returns to the previously viewed programme.

+ ∠ − Adjusts the volume level.

FAV Accesses your favourite programme list.

RATIO Resizes an image.

MUTE ☞ Mutes all sounds.

MUTE ज़ * Accesses the [Accessibility] menu.

ightarrow P
ightarrow Scrolls through the saved programmes.

PAGE Moves to the previous or next screen.

GUIDE Shows programme guide.

PORTAL Displays and removes hotel interactive menu.

INFO () Views the information of the current programme and screen. **Navigation buttons (up/down/left/right)** Scrolls through menus or options.

OK • Selects menus or options and confirms your input.

SETTINGS Accesses the main menus.

⇒ (BACK) Returns to the previous level.

EXIT Clears on-screen displays and return to TV viewing.

SUBTITLE Recalls your preferred subtitle in digital mode.

Control buttons (■, ▶, II, ◄◀, ▶►) Controls media contents. () mpunk Accesses the AV devices connected with the HDMI cable through HDMI-CEC. Opens the SIMPLINK menu.

O.MENU Accesses the Quick menus

AD Audio descriptions function will be enabled.

ALARM This function is not supported.



- Do not mix new batteries with old batteries. This may cause the batteries to overheat and leak.
- Failure to match the correct polarities of the battery may cause the battery to burst or leak, resulting in fire, personal injury, or ambient pollution.
- This apparatus uses batteries. In your community there might be regulations that require you to dispose of these batteries properly due to environmental considerations.
 Please contact your local authorities for disposal or recycling information.
- The product's internal and external batteries should not be
 exposed to excessive heat such as direct sunlight, fire, or
 the like.
- In Analogue TV and some countries, some remote control buttons may not work.

Troubleshooting

Cannot control the TV with the remote control.

- · Check the remote control sensor on the product and try again.
- Check if there is any obstacle between the product and the remote control.
- Check if the batteries are still working and properly installed (\oplus to \oplus , \odot to \odot).

No image display and no sound is produced.

- · Check if the product is turned on.
- Check if the power cord is connected to a wall outlet.
- Check if there is a problem in the wall outlet by connecting other products.

The TV turns off suddenly.

- Check the power control settings. The power supply may be interrupted.
- Check if the auto-off function is activated on the settings related time.
- If there is no signal while the TV is on, the TV will turn off automatically after 15 minutes of inactivity.

When connecting to the PC (RGB/HDMI), no signal is detected.

- Turn the TV off/on using the remote control.
- Reconnect the RGB/HDMI cable.
- Restart the PC with the TV on.

Abnormal display

- If the product feels cold to the touch, there may be a small "flicker" when it is turned on. This is normal, there is nothing wrong with product.
- This panel is an advanced product that contains millions of pixels. You may see tiny black dots and/or brightly coloured dots (red, blue or green) at a size of 1 ppm on the panel. This does not indicate a malfunction and does not affect the performance and reliability of the product. This phenomenon also occurs in third-party products and is not subject to exchange or refund.
- You may find different brightness and colour of the panel depending on your viewing position(left/right/top/down).
 This phenomenon occurs due to the characteristic of the panel. It is not related with the product performance, and it is not malfunction.
- Displaying a still image for a prolonged period of time may cause image sticking. Avoid displaying a fixed image on the TV screen for a long period of time.

Generated sound

- "Cracking" noise: A cracking noise that occurs when watching or turning off the TV is generated by plastic thermal contraction due to temperature and humidity. This noise is common for products where thermal deformation is required.
- Electrical circuit humming/panel buzzing: A low level noise is generated from a high-speed switching circuit, which supplies a large amount of current to operate a product. It varies depending on the product. This generated sound does not affect the performance and reliability of the product.

Â

 When cleaning the product, be careful not to allow any liquid or foreign objects to enter the gap between the upper, left or right side of the panel and the guide panel. (Depending on model)



- Make sure to wring any excess water or cleaner from the cloth.
- Do not spray water or cleaner directly onto the TV screen.
- Make sure to spray just enough of water or cleaner onto a dry cloth to wipe the screen.

Specifications

(Depending on country)

| Broadcasting Specifications (-T*) | | |
|---------------------------------------|--------------------------------|----------------------------------|
| | Digital TV | Analogue TV |
| | (Depending on Country & Model) | (Depending on Country) |
| | DVB-T/T2 | PAL B/B, PAL B/G, PAL D/K, PAL-I |
| Television system | DVB-C | SECAM B/G, SECAM D/K |
| | | NTSC-M |
| Programme coverage | VHF, UHF VHF, UHF, CATV | |
| Maximum number of storable programmes | 2,000 | |
| External antenna impedance | 75 Ω | |
| CI Module (W x H x D) | 100.0 mm x 55.0 mm x 5.0 mm | |

* Only DVB-T2 support models. (Despite DVB-T2 Model, DVB-T/T2 does not apply in Philippine)

(Depending on country)

| Broadcasting Specifications (-G*) | | | | |
|--|-------------------------------|--------------|----------------------------------|--------------|
| | | Digital TV | | Analogue TV |
| Television system | DVB-S/S2 DVB-T/T2 DVB-C | | PAL/SECAM B/G, D/K, I SECAM L | |
| | DVB-S/S2 | DVB-C | DVB-T/T2 | |
| | | | VHF III : 174 ~ 230 MHz | |
| Channel coverage | 950~2,150 MHz | 46 ~ 890 MHz | UHF IV : 470 ~ 606 MHz | 46 ~ 862 MHz |
| (Band) | | | UHF V : 606 ~ 862 MHz | 10 002 11112 |
| | | | S Band II : 230 ~ 300 MHz | |
| | | | S Band III : 300 ~ 470 MHz | |
| Maximum number of storable programmes | 6,000 | 2,000 | | |
| External antenna impedance | 75 Ω | | | |
| CI Module (W x H x D) | 100.0 mm x 55.0 mm x 5.0 mm | | | |

| Environment condition | | |
|-------------------------------------|-----------------|--|
| Operating Temperature 0 °C to 40 °C | | |
| Operating Humidity | Less than 80 % | |
| Storage Temperature | -20 °C to 60 °C | |
| Storage Humidity | Less than 85 % | |

HDMI-DTV supported mode

| Resolution | Horizontal Frequency (kHz) | Vertical Frequency (Hz) |
|--------------|-------------------------------|----------------------------|
| 640 x 490p | 31.46 | 59.94 |
| 640 x 480p | 31.50 | 60.00 |
| 720 x 480p | 31.469 | 59.94 |
| 720 X 460p | 31.50 | 60.00 |
| 720 x 576p | 31.250 | 50.00 |
| | 37.50 | 50.00 |
| 1280 x 720p | 45.00 | 60.00 |
| | 44.96 | 59.94 |
| | 28.125 | 50.00 |
| 1920 x 1080i | 33.75 | 60.00 |
| | 33.72 | 59.94 |
| | 56.250 | 50.00 |
| | 67.50 | 60.00 |
| | 67.432 | 59.94 |
| 1920 x 1080p | 27.00 | 24.00 |
| | 26.973 | 23.976 |
| | 33.75 | 30.00 |
| | 33.716 | 29.976 |

HDMI-PC supported Mode

- PC audio is not supported.
- Use HDMI IN 1 for PC mode. (Depending on model)

| Resolution | Horizontal Frequency (kHz) | Vertical Frequency (Hz) |
|--------------------------|-------------------------------|----------------------------|
| 640 x 350 | 31.468 | 70.09 |
| 720 x 400 | 31.469 | 70.08 |
| 640 x 480 | 31.469 | 59.94 |
| 800 x 600 | 37.879 | 60.31 |
| 1024 x 768 | 48.363 | 60.00 |
| 1152 x 864 | 54.348 | 60.053 |
| 1360 x 768 | 47.712 | 60.015 |
| 1280 x 1024 ¹ | 63.981 | 60.020 |
| 1920 x 1080 ¹ | 67.50 | 60.00 |

1 Only 43/49LT34*

Component port connecting information

| Component ports on the TV | Y | P _B | P _R |
|----------------------------------|---|----------------|----------------|
| | Y | P _B | P _R |
| Video output ports on DVD player | Y | B-Y | R-Y |
| | Y | Cb | Cr |
| | Y | Pb | Pr |

| Signal | Component |
|--------------|-----------|
| 480i / 576i | 0 |
| 480p / 576p | 0 |
| 720p / 1080i | 0 |
| 1080p | 0 |

RGB-PC supported mode

| Resolution | Horizontal Frequency (kHz) | Vertical Frequency (Hz) |
|--------------------------|-------------------------------|----------------------------|
| 640 x 350 | 31.468 | 70.09 |
| 720 x 400 | 31.469 | 70.08 |
| 640 x 480 | 31.469 | 59.94 |
| 800 x 600 | 37.879 | 60.31 |
| 1024 x 768 | 48.363 | 60.00 |
| 1152 x 864 | 54.348 | 60.053 |
| 1360 x 768 | 47.712 | 60.015 |
| 1280 x 1024 ¹ | 63.981 | 60.020 |
| 1020 - 10001 | 66.587 | 59.934 |
| 1920 x 1080 ¹ | 67.50 | 60.00 |

1 Only 43/49LT34*

My Media Supported Files

- Maximum data transfer rate: 20 Mbps (Mega bit per second)
- External supported subtitle formats: *.srt, *.smi, *.sub (Only for SubViewer 1.0/2.0), *.ass, *.ssa, *.txt

Supported Photo Formats

| Extension | ltem | Resolution |
|--------------|------------------------|--|
| | | SOFO : Baseline |
| | Available File Type | SOF1 : Extend Sequential |
| | ijpe | SOF2 : Progressive |
| .jpeg, .jpg, | | Minimum: 64 (W) x 64 (H) |
| .jpe | Photo Size | Maximum (Normal Type): 15360 (W) x 8640 (H) |
| | | Maximum (Progressive Type): 1920 (W) x 1440 (H) |
| have | Photo Size | Minimum: 64 (W) x 64 (H) |
| .bmp | | Maximum: 9600 (W) x 6400 (H) |
| | Available File Type | Interlace, Non-Interlace |
| | | Minimum: 64 (W) x 64 (H) |
| .png | Photo Size | Maximum (Interlace): |
| | | 1200 (W) x 800 (H) |
| | | Maximum (Non-Interlace): |
| | | 9600 (W) x 6400 (H) |

• BMP and PNG format files may be slower to display than JPEG.

• Non-standard photo/image file may not be displayed.

Supported Audio Formats

| File type | ltem | Info |
|--------------|--------------|--|
| | Bit rate | 32 Kbps - 320 Kbps |
| mp3 | Sample freq. | 16 kHz - 48 kHz |
| | Support | MPEG-1, MPEG-2, Layer2, Layer3 |
| | Bit rate | Free Format |
| AAC | Sample freq. | 8 kHz - 48 kHz |
| | Support | ADIF, ADTS |
| | Bit rate | Free Format |
| M4A | Sample freq. | 8 kHz - 48 kHz |
| | Support | MPEG-4 |
| | Bit rate | 128 Kbps ~ 320 Kbps |
| WMA | Sample freq. | 8 kHz - 48 kHz |
| | Support | WMA7, WMA8, WMA9 Standard |
| | Bit rate | ~ 768 Kbps |
| WMA 10 | Channel / | M0: up to 2 Channel @ 48 kHz (Except LBR mode), |
| Pro | Sample freq. | M1: up to 5.1 Channel @ 48 kHz, |
| | | M2: up to 5.1 Channel @ 96 kHz |
| | Support | WMA 10 Pro |
| | Bit rate | Free Format |
| OGG | Sample freq. | 8 kHz - 48 kHz |
| | Support | OGG Vorbis |

Supported Video Formats

- Maximum: 1920 x 1080 @ 30p (only Motion JPEG 640 x 480 @ 30p)
- H.264/AVC is supported profile level 4.1 or below.

| Extension | Codec | |
|-------------------------------|-------|--|
| .asf .wmv | Video | MPEG-4 Part2, XViD, H.264/AVC, VC1(WMV3, WVC1) |
| | Audio | WMA Standard, WMA9(Pro), MP3, AAC, AC3 |
| .avi | Video | MPEG-2, MPEG-4 Part2, XViD, H.264/AVC |
| | Audio | HE-AAC, LPCM, ADPCM, MPEG-1 Layer I, MPEG-1 Layer II, Dolby Digital, MPEG-1 Layer III (MP3) |
| .ts, .trp, .tp .mts, .m2ts | Video | H.264/AVC, MPEG-2, H.265/HEVC |
| | Audio | MPEG-1 Layer I, MPEG-1 Layer II, MPEG- 1 Layer III (MP3), Dolby Digital, Dolby Digital Plus, AAC, HE-AAC |
| .vob | Video | MPEG-1, MPEG-2 |
| | Audio | Dolby Digital, MPEG-1 Layer I, MPEG-1 Layer II, DVD-LPCM |
| .mp4, .m4v | Video | MPEG-2, MPEG-4 Part2, XVID, H.264/AVC |
| .mov | Audio | AAC, MPEG-1 Layer III (MP3) |
| .mkv | Video | MPEG-2, MPEG-4 Part2, XViD, H.264/AVC |
| | Audio | HE-AAC, Dolby Digital, MPEG-1 Layer III (MP3), LPCM |
| .mpg, .mpeg .mpe | Video | MPEG-1, MPEG-2 |
| | Audio | MPEG-1 Layer I, MPEG-1 Layer II, Dolby Digital, LPCM |
| .dat | Video | MPEG-1, MPEG-2 |
| | Audio | MP2 |
| .flv | Video | Sorenson H.263, H.264/AVC |
| | Audio | MP3, AAC, HE-AAC |
| .3gp | Video | H.264/AVC, MPEG-4 Part2 |
| | Audio | AAC, AMR(NB/WB) |

Open Source Software Notice Information

To obtain the source code under GPL, LGPL, MPL, and other open source licenses, that is contained in this product, please visit http://opensource.lge.com.

In addition to the source code, all referred license terms, warranty disclaimers and copyright notices are available for download.

LG Electronics will also provide open source code to you on CD-ROM for a charge covering the cost of performing such distribution (such as the cost of media, shipping, and handling) upon email request to *opensource@lqe.com*.

This offer is valid for a period of three years after our last shipment of this product. This offer is valid to anyone in receipt of this information.

Licenses

Supported licenses may differ by model.



The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.

Manufactured under license from Dolby Laboratories. Dolby, Dolby Vision, Dolby Audio, Dolby Atmos, and the double-D symbol are trademarks of Dolby Laboratories.

(Depending on model)





The model and serial number of the product are located on the back and on one side of the product. Record them below in case you ever need service.

| MODEL | |
|-----------|--|
| SERIAL NO | |