

The Ultimate Visibility Enhancement
BRIGHTEST OUTDOOR DISPLAY WX50MF



WX50MF 47"

LED HIGH VISIBILITY
High Brightness



SHINE-OUT

Perfect fit for window display by reflecting away the sunlight for best image visibility and clearer display under direct sunlight than conventional panel.



EASY TO CUSTOMIZE (OPEN FRAME)

WX50MF fits to any customer need and circumstance with its open frame. It can be designed according to customer request at an affordable price.



BRIGHTEST OUTDOOR DISPLAY

WX50MF 47F"



FEATURES

- LED (PD Panel)
- High Brightness : 2,000nit
- Shine-Out
- No Blackening Defect (Tni : 110°C)
- Easy Customization (Open Frame)
- Built-in FANs for Optimal Ventilation (Air Curtain Cooling)

SPECIFICATIONS

WX50MF

PANEL	Screen Size	47F" Class (46.96" measured diagonal)
	Panel Technology	IPS
	Aspect Ratio	16 : 9
	Native Resolution	1920 x 1080 (FHD)
	Brightness	2000nit
	Contrast Ratio	1,300 : 1
	Dynamic CR	500,000 : 1
	Viewing Angle (H x V)	178 x 178
	Response Time	8ms (G to G, *WOT)
CONNECTIVITY		
	Input (Rear)	
	Digital	HDMI(1), DVI(1), Display Port(1) with HDCP for all input
	Analog	Component(1), AV(1), RGB(1) (Shared with D-Sub)
	Audio	PC / AV / Component Audio In(1)
	External Control	RS232C(1), RJ45(1)
	USB	USB(1)
	Output (Rear)	
	Digital	DVI-D(1)
	Analog	Component(1), Composite(1), RGB(1) (Shared with D-Sub)
	Audio	External Speaker
	External Control	RS232C
	Audio	
	Auto Volume	No
	Balance	Yes
	Audio Power	20W (10W x 2)
	Speaker On / Off	Yes
	Clear Voice II	Yes
	Sound Mode	Standard, Music, Cinema, Sports, Game
PHYSICAL SPECIFICATION		
	Bezel Width	11mm
	Monitor Dimension (W x H x D)	107.08cm x 66.55cm x 15.7cm
	Weight (head)	23.9kg

	Carton Dimensions (W x H x D)	118.2cm x 74.3cm x 26.9cm
	Packed Weight	29.1kg
	VESA™ Standard Mount Interface	N/A
SPECIAL FEATURES	Additional	Temp sensor, Ambient sensor, 15 x 15 Tile mode, Shine-out, Media Player integrated solution
ENVIRONMENT CONDITIONS	Operation Temperature	0°C - 40°C
	Operation Humidity	10% - 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Consumption	
	Typical / Smart Energy Saving (on)	240W / 120W
	DPMS	1.0W (Set only)
	Power Off	0.5W
STANDARD(CERTIFICATION)	Safety	UR / cUR / CB scheme / TUV-Type
	EMC	FCC Class "A" / CE / KCC
	ErP / Energy Star	No
MEDIA PLAYER COMPATIBILITY	Slot PC Compatible (optional)	Yes
	External Media Player Attachable	No
SOFTWARE COMPATIBILITY	Supersign Compatibility	Elite-w / Elite-w lite
ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual

* WOT : Within Operation Temperature

※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

INTERFACE



DIMENSION (unit : mm)

