

# NEC V302H

Order Code: 60003897

NEC Value Projector



The compact size in combination with light weight makes the V Series easy to place it wherever you need it. With 3000 ANSI lumens brightness and 8.000:1 contrast, this compact projector is recommended for screen sizes of up to 115" diagonal in typical office environments.

The excellent price performance ratio makes this projector especially suitable for classrooms and mid-sized meeting rooms.

## BENEFITS

**Excellent price performance ratio** - due to a rich feature set.

**Great picture quality** - thanks to Full HD resolution and 8.000:1 contrast.

**3D ready** - future-proof DLP®-Link™ technology with 144 Hz and Top/Bottom, 60 Hz.

**Full media playback capabilities** - with 8W speaker and 3D support.

**Future-proof connectivity** - incl. MHL and network support.



ERP  
COMPLIANT



NaViSet  
Administrator 2

|                             |                                      |  |
|-----------------------------|--------------------------------------|--|
| <b>IMAGE</b>                | Projection Technology                | 1-chip DLP™ Technology   |
|                             | Native Resolution                    | 1920 x 1080 (Full HD)  |
|                             | Aspect Ratio                         | 16:9   |
|                             | Contrast Ratio <sup>1</sup>          | 8000:1   |
|                             | Brightness <sup>1</sup>              | 3000 ANSI Lumen  |
|                             | Lamp                                 | 218 W AC   |
|                             | Lamp Life [hrs]                      | 6000 Eco (3500 High Bright Mode)   |
|                             | Lens Offset [%]                      | 66.4   |
|                             | Projection Factor                    | 1.5 – 1.8 : 1  |
|                             | Projection Distance [m]              | 1.3 – 12   |
|                             | Screen Size (diagonal) [cm] / [inch] | Maximum: 762 / 300"; Minimum: 102 / 40"  |
|                             | Zoom                                 | Manual   |
|                             | Focus Adjustment                     | Manual   |
|                             | Supported Resolutions                | Up to 1920x1080  |
|                             | Frequency                            | Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz   |
| <b>CONNECTIVITY</b>         | RGB (analog)                         | Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr)<br>Output: 1 x Mini D-sub 15 pin   |
|                             | HDMI™                                | Input: 1 x HDMI™ (Deep Color, Lip sync); 1 x HDMI™ with MHL support  |
|                             | Video                                | Input: 1 x RCA   |
|                             | Audio                                | Input: 1 x RCA Stereo for Video and S-Video; 2 x 3.5 mm Stereo Mini Jack<br>Output: 1 x 3.5 mm Stereo Mini Jack  |
|                             | Control                              | Input: 1 x D-Sub 9 pin (RS-232) (male)   |
|                             | LAN                                  | 1 x RJ45   |
|                             | USB                                  | 1 x Mini USB   |
|                             | Video Signals                        | NTSC; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM   |
| <b>REMOTE CONTROL</b>       | Remote Control                       | Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; Freeze-function; Help-function; ID set; Keystone Correction; Lamp Mode Control; Magnify-function; Picture Adjust; Picture Mode; Picture Mute; Source Select  |
| <b>ELECTRICAL</b>           | Power Supply                         | 100-240 V AC; 50 - 60 Hz   |
|                             | Power Consumption [W]                | 266 (High Bright) / 207 (Eco) / 3 (Network Stand-by) / 0.5 (Stand-by)  |
| <b>MECHANICAL</b>           | Dimensions (W x H x D) [mm]          | 324 x 88 x 250 (without lens and feet)   |
|                             | Weight [kg]                          | 2.9  |
|                             | Fan Noise [dB (A)]                   | 32 / 35 (Eco / Normal)   |
| <b>ERGONOMICS</b>           | Safety and Ergonomics                | CE; ErP; RoHS; TÜV GS  |
|                             | Speakers [W]                         | 1 x 8 (mono)   |
| <b>ADDITIONAL FEATURES</b>  | Special Characteristics              | 3D ready DLP®-Link™, 144 Hz and Top/Bottom, 60 Hz; 6-segment Colour Wheel; Auto Power Start; BrilliantColor™ and VIDi technology; Carbon Savings Meter; Crestron RoomView; Keystone Correction (H=±30°, V=±30°); Long Life Lamp; NaViSet Administrator 2; Off-Timer; Plug & Play; Quick-Start-/Direct-Power-Off Function; Virtual Remote for direct PC control |
| <b>GREEN FEATURES</b>       | Energy Efficiency                    | Intelligent Power Management   |
|                             | Ecological Materials                 | 100% recyclable packaging; Downloadable manuals  |
|                             | Ecological Standards                 | ErP compliant; RoHS compliant; WEEE  |
| <b>WARRANTY</b>             | Projectors                           | 3 years pan-European service   |
|                             | Light Source                         | 6 months, max. 1000 hrs  |
| <b>SHIPPING CONTENT</b>     | Shipping Contents                    | IR Remote Control (RD-469E); Lens Cap; Mini D-SUB Signal Cable (1.8 m); Power Cord; Projector; Quick Setup Guide; Users Manual   |
| <b>OPTIONAL ACCESSORIES</b> | Optional Accessories                 | 3D Starter Kit (NP01SK3D); DLP-Link 3D Glasses (NP02GL/VolfoniFit); Lamp (NP35LP); Universal Ceiling Mounts (PJ01UCM)  |

<sup>1</sup> Compliance with ISO21118-2005