Productive, compact mono laser All-In-Ones with network connectivity and tilt and touch- screen control panel



you can





# Network ready All-In-Ones device with touch-screen control panel for small offices demanding high productivity

Fast and efficient mono laser All-In-Ones offering print, copy, scan and fax functions in one convenient, compact device. Operation is easy thanks to a tilting control panel and one-touch solution keys.

### **Key Features**

- Productive, mono laser All-In-One for a busy small office with print, copy, scan and fax functions
- Wi-Fi and Ethernet: seamlessly share functions and easily print from PCs, smartphones, tablets (requires Wi-Fi connection)
- Ethernet connectivity for seamless network sharing of functions and easy printing from PCs
- No waiting for documents with Canon's Quick First-Print technologies plus 23ppm
- Integrated 35-sheet ADF and a 250-sheet paper cassette
- Easy operation with tilting operation panel and large touch screen LCD
- Capture all the detail in originals with up to 9600 x 9600 dpi colour scanning
- Efficient scanning and copying workflows with quick one-touch solution keys
- Save time and money with market leading energy efficiency
- Stylish, space saving design with Quite Mode operation
- Apple AirPrint™ and Mopria printing support (requires Wi-Fi connection)

## What's in the Box

Main Unit, Starter Cartridge, Power Cord, Telephone Line Cable, Hand Set Clamp, Starter Guide, Warranty Card, User Software CD-ROM

#### Dimensions (W x D x H)

390 mm x 371 mm x 312 mm

#### Supported OS

Windows Windows@8.1, Windows@8, Windows@7, Windows@XP, Windows@Vista, Windows@ Server 2012 R2 (NW Model only), Windows@ Server 2012 (NW Model only), Windows@ Server 2008 R2 (NW Model only), Windows@ Server 2008 (NW Model only), Windows@ Server 2003 (NW Model only)

Mac OS X 10.5.8 or later Linux OS is support by Linux Driver v3.00 or later version

















# Specification for MF216n





Machine type Available functions	Mono Laser All-in-One Print, Copy, Scan & Fax
PRINTER Print speed Printing method Print quality Print resolution First Print Out Time Printer languages Print margins Toner saver mode	Up to 23 ppm (A4) Monochrome laser beam printing Up to 1200 x 1200 dpi with Automatic Image Refinement 600 x 600 dpi 6 secs or less UFR II LT 5 mm-top, bottom, left and right (other sizes than envelope) 10 mm-top, bottom, left and right (envelope) Yes
COPIER Copy speed First Copy Output Time (FCOT) Copy resolution Copy modes Multiple copy Reduction / Enlargement Toner saver mode Other features	Up to 23 ppm (A4) Approx. 9.0 or less (A4) Up to 600 x 600 dpi Text, Text/Photo, Text/Photo+, Photo Up to 99 copies 25-400% in 1% increments Yes Memory Sort, 2 on 1, 4 on 1, ID Card Copy
SCANNER Type Scan resolution  Colour scanning depth Greyscales Compatibility Max. scan width	Colour Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi 24-bit 256 levels TWAIN, WIA 216 mm
FAX Modem speed Receive mode Fax resolution  FAX memory Speed dials Group dials/destinations Sequential broadcast Memory backup Other features	Super G3 33.6kbps FAX Only, Manual, Answering, Fax / Tel Auto SW Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Up to 256 pages¹ Max. 104 (including 4 one-touch dials) Max.104 destinations Max. 114 locations Flash Memory Back-up FAX Forwarding, Dual Access, Remote Reception, PC FAX(TX only), DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports
Media handling Scanner type Paper input (Standard) Paper output Media types Media sizes	Flatbed and Automatic Document Feeder (ADF) 250-sheet tray 35-sheet ADF (80g/m2 or less) 100-sheet Plain, heavy, Recycled, Transparency, Label, Envelope Tray: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard, AFLS Envelope: COM10, Monarch, C5, DL, Custom sizes: Min. 76.2 x 210 mm to Max. 216 x 356 mm Multi-purpose tray: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard,AFLS Envelope: COM10, Monarch, C5, DL, Custom sizes (Min. 76.2 x 127 mm to Max. 216 x 356 mm) ADF: A4, B5, A5, B6, LTR, LGL Min. 105 x 148 mm to Max. 356 x 216 mm Tray: 60 to 163 g/m² Multi-purpose tray: 60 to 163 g/m²

INTERFACE & SOFTWARE Interface type	USB 2.0 Hi-speed,10BASE-T/100BASE-TX
Operating System compatibility	Windows@8.1 Windows@8 Windows@7 Windows@XP
	Windows@Vista Windows@ Server 2012 R2² Windows@ Server 2012² Windows@ Server 2008 R2² Windows@ Server 2008 R2² Windows@ Server 2008²
	Windows@ Server 2003 <sup>2</sup> Mac OS X 10.5.8 or later Linux <sup>3.4</sup>
Software and printer management	Remote User Interface (RUI), Printer driver, Fax driver, Scanner driver, MF Toolbox, AddressBookTool, Presto! PageManager, Toner Status Tool
GENERAL FEATURES	Mary 0.000 and a state of the
Duty cycle Memory	Max. 8,000 pages per month 256 MB
Control panel Dimensions with trays	6-line LCD B&W Touch Screen 390 mm x 441 mm x 360 mm
(W x D x H)	390 111111 x 441 111111 x 300 111111
Installation space (W x D x H)	429 mm x 490 mm x 630 mm
Weight	Approx 11.5 Kg
Power Source Power Consumption	AC 220 to 240V : 50/60Hz Maximum: Approx. less than 1270 W
rower Consumption	Active: Approx. less than 500 W
	Stand by mode: Approx. 5.4W
	Sleep mode: Approx. 1.6 W Typical Electricity Consumption (TEC): 0.8 kWh/week
Noise Levels	Sound pressure <sup>5</sup> :
	Active: 50dB (Quiet Mode: 45dB)
	Standby: Inaudible Sound Power Level <sup>5</sup> :
	Active: 6.5B (Quiet Mode: 6.0B)
	Standby : 43dB or less
CONSUMABLES	
Cartridges	Cartridge 737 (2,400 pages <sup>6</sup> ) <sup>7</sup>
Footnote  11 Based on ITU-T Standard Chart No. 1 22 Network scanning not supported 13 Web distribution only 14 Web distribution only release date Af 15 Tested in accordance to ISO/T79 and 16 Ships with 1,700 pages starter cartic.	declared per ISO9296.
71 Based on ISO/IEC 19752	



**Standard disclaimers**All specifications subject to change without notice

















Canon Europe canon-europe.com

English Edition © Canon Europa N.V., 2014

