

## C-17P



**Incredible value and performance: a solid 17" display choice for reliability in home and office environments.**

---

The highly-affordable C-17P offers the vivid image quality, convenient inputs for analogue and digital signals, crisp 1,000:1 typical contrast ratio, as well as built-in speakers for multi-media entertainment. With a sleek design and VESA compatible wall mounts that allow for a variety of mounting options, the C-17P is designed perfectly for home use or multi-display office environments where cost is a consideration.

---

- > Slim and sleek design
- > Economical and durable concern
- > Fast 3ms response time
- > Crisp 1,000:1 typical contrast ratio
- > Built-in speakers (3W x 2)
- > Tilt from -5 ° to +20 ° for optimal viewing
- > VESA standard wall mount
- > WEEE, RoHS, REACH certified

# C-17P

## Specifications

## C-17P

<b>Panel</b>	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments  Viewing Angle (H/V) Display Colour Response Time	TFT LCD 17.0" (432 mm) SXGA 1280 x 1024 0.264 mm 250cd/m2 (Typical) 1,000:1 (Typical) Hard Coating (3H), Anti-glare treatment 170°/170° (Typical) 16.7M 3ms (GTG)
<b>Frequency (H/V)</b>		H: 30 kHz - 82 kHz V: 56 Hz - 75 Hz
<b>Input</b>	Analogue Digital	15-Pin D-Sub 24-Pin DVI-D
<b>Audio</b>	Audio In Speaker	1 x Stereo audio in for PC (audio jack, 3.5ø) 3W x 2
<b>Power</b>	Power Supply Power Requirements Consumption	Internal AC 100 - 240 V, 50 - 60 Hz < 22 W (On) < 0.5 W (Stand-by) < 0.5 W (Off)
<b>Plug &amp; Play</b>	VESA	DCC 2B
<b>Operating Conditions</b>	Temperature Humidity	0 °C ~ 40 °C 10% ~ 85%
<b>Storage Conditions</b>	Temperature Humidity	-25 °C ~ 55 °C 10% ~ 85%
<b>Mounting</b>	VESA FPMPMI	Yes (100 x 100mm)
<b>Tilt</b>	Tilt	-5° ~ +20°
<b>Dimensions</b>	Product (W x H x D) Packaging (W x H x D)	384 x 358 x 195 mm (15.1" x 14.1" x 7.7") 417 x 397 x 136 mm (16.4" x 15.6" x 5.4")
<b>Weight</b>	Product Weight Packaged Product Weight	3.5 kg (7.7 lbs) 4.7 kg (10.3 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	FCC, CB, CE, GOST-R, WEEE, RoHS, REACH
<b>Accessories</b>	Supplied	User manual, 15-Pin D-Sub cable, audio cable, AC power cord



Sleek design with anti-glare display panel for superior viewing comfort



VESA standard wall mount allows for secure mounting



Built-in speakers provide easy access to multimedia applications



Tilt from -5 °C to +20 °C for optimal viewing

