

## Product Highlights

### Full HD Image Quality and Detail

A high-resolution megapixel sensor provides Full HD 1080p resolution images and video to ensure that you capture the details you need

### Vandal Resistant Outdoor Surveillance

With both IK10 and IP66 ratings, the DCS-6210 is ideal for the most demanding of surveillance applications

### Precision Positioning

A 3-axis gimbal allows manual positioning of the lens at any angle



## DCS-6210

# Full HD Mini Fixed Dome Network Camera

## Features

### Camera

- 1/2.7" 2 megapixel progressive CMOS sensor
- Megapixel Fixed lens: 4.3 mm F2.0
- Built-in microphone
- IP66 weatherproof
- IK10 vandal-proof
- ONVIF compliant

### Connections

- 10/100 Fast Ethernet port with PoE
- microSD/SDHC Card slot for onboard storage

### Image & Video

- Real-time H.264/ MPEG-4/ MJPEG
- Max. resolution 1920x1080 at 15 fps
- 1280x720 at 30fps
- Simultaneous streams
- ePTZ for virtual PTZ operation
- Motion detection
- Privacy mask
- Samba client for NAS
- Multiple access lists

## Built for Tough Environments

Specially designed for use in challenging environments the DCS-6210 has a compact rugged, metal, IK10 (vandalproof) and IP66 (weatherproof) housing. This means that it is able to withstand sudden high impact, and adverse weather conditions. Additionally, the DCS-6210 has a Power over Ethernet (PoE) port which allows you to connect the camera to your network and power it through a single cable. This both expands and simplifies your deployment options by eliminating the need for a nearby power outlet, making deployment on ceilings much easier.

## Surveillance in Full High Definition

The D-Link DCS-6210 features a 1/2.7" 1080p Full HD 2 Megapixel CMOS image sensor providing high definition video up to 1920x1080 resolution. A 1080p sensor is nearly seven times the resolution of a VGA sensor. This ensures the video has the additional clarity required for person, object and vehicle identification


## A Complete, Expandable Surveillance Solution

The DCS-6210 is a self-sufficient surveillance solution, capable of recording snapshots and video to a microSD card without requiring a PC or network storage device.

If you want to expand your surveillance options, D-ViewCam management software is also included, giving you the ability to manage up to 32 cameras with a robust set of features, including multi-camera views and automated e-mail alerts to keep you informed of suspicious or unusual activities.

Technical Specifications		
Camera		
Camera Hardware Profile	<ul style="list-style-type: none"> <li>• 1/2.7" 2 Megapixel progressive CMOS sensor</li> <li>• Fixed Lens, focal length 4.3 mm, aperture F2.0</li> <li>• 10x digital zoom</li> </ul>	<ul style="list-style-type: none"> <li>• Field of view:               <ul style="list-style-type: none"> <li>• (H) 79°</li> <li>• (V) 43°</li> <li>• (D) 90°</li> </ul> </li> </ul>
Camera Housing	<ul style="list-style-type: none"> <li>• IP66 weatherproof</li> </ul>	<ul style="list-style-type: none"> <li>• IK10 vandalproof</li> </ul>
Image Features	<ul style="list-style-type: none"> <li>• Configurable image size, quality, frame rate, and bitrate</li> <li>• Time stamp and text overlays</li> <li>• Configurable motion detection windows</li> </ul>	<ul style="list-style-type: none"> <li>• Configurable privacy mask zones</li> <li>• Configurable white balance, brightness, saturation, contrast, sharpness, and BLC</li> </ul>
Video Compression	<ul style="list-style-type: none"> <li>• Simultaneous H.264/MPEG-4/MJPEG format compression</li> </ul>	<ul style="list-style-type: none"> <li>• JPEG for still images</li> </ul>
Video Resolution	<ul style="list-style-type: none"> <li>• 16:9 - 1920 x 1080 (up to 15 fps) 1280 x 800, 1280 x 720, 800 x 450, 640 x 360, 480 x 270, 320 x 176, 176 x 144 up to 30 fps recording<sup>1</sup></li> </ul>	<ul style="list-style-type: none"> <li>• 4:3 - 1440 x 1080 (up to 25 fps) 1024 x 768, 800 x 600, 640 x 480, 480 x 360, 320 x 240, 176 x 144 up to 30 fps recording<sup>1</sup></li> </ul>
Audio Support	<ul style="list-style-type: none"> <li>• G.726</li> </ul>	<ul style="list-style-type: none"> <li>• G.711</li> </ul>
External Device Interface	<ul style="list-style-type: none"> <li>• 10/100 BASE-TX Fast Ethernet port</li> <li>• Supports 802.3af PoE</li> </ul>	<ul style="list-style-type: none"> <li>• microSD/SDHC card slot</li> </ul>
Network		
Network Protocols	<ul style="list-style-type: none"> <li>• IPv6</li> <li>• IPv4</li> <li>• TCP/IP</li> <li>• UDP</li> <li>• ICMP</li> <li>• DHCP client</li> <li>• NTP client (D-Link)</li> <li>• DNS client</li> <li>• DDNS client (D-Link)</li> <li>• SMTP client</li> <li>• FTP client</li> </ul>	<ul style="list-style-type: none"> <li>• HTTP / HTTPS</li> <li>• Samba client</li> <li>• PPPoE</li> <li>• UPnP port forwarding</li> <li>• RTP / RTSP / RTCP</li> <li>• IP filtering</li> <li>• QoS</li> <li>• CoS</li> <li>• IGMP</li> <li>• ONVIF compliant</li> </ul>
Security	<ul style="list-style-type: none"> <li>• Administrator and user group protection</li> <li>• Password authentication</li> </ul>	<ul style="list-style-type: none"> <li>• HTTP and RTSP digest encryption</li> </ul>
System Management		
System Requirements for Web Interface	<ul style="list-style-type: none"> <li>• Browser: Internet Explorer, Firefox, Safari, Chrome</li> </ul>	
Event Management	<ul style="list-style-type: none"> <li>• Motion detection</li> <li>• Event notification and uploading of snapshots/video clips via e-mail or FTP</li> </ul>	<ul style="list-style-type: none"> <li>• Supports multiple SMTP and FTP servers</li> <li>• Multiple event notifications</li> <li>• Multiple recording methods for easy backup</li> </ul>
Remote Management	<ul style="list-style-type: none"> <li>• Take snapshots/video clips and save to local hard drive or NAS via web browser</li> </ul>	<ul style="list-style-type: none"> <li>• Configuration interface accessible via web browser</li> </ul>
D-ViewCam™ System Requirements	<ul style="list-style-type: none"> <li>• Operating System: Microsoft Windows 7/Vista/XP</li> <li>• Web Browser: Internet Explorer 7 or higher</li> </ul>	<ul style="list-style-type: none"> <li>• Protocol: Standard TCP/IP</li> </ul>
D-ViewCam™ Software Functions	<ul style="list-style-type: none"> <li>• Remote management/control of up to 32 cameras</li> <li>• Viewing of up to 32 cameras on one screen</li> <li>• Scheduled motion triggered, or manual recording options</li> </ul>	<ul style="list-style-type: none"> <li>• Supports all management functions in web interface</li> </ul>

# DCS-6210 Full HD Mini Fixed Dome Network Camera

Physical	
Weight	• 14.5oz (412 g) ± 5%
Power Consumption	• 8.6 watts ± 5%
Temperature	• Operating: -13° to 122°F (-25 to 50 °C)      • Storage: -4° to 158°F (-20 to 70 °C)
Humidity	• Operating: 20% to 80% non-condensing      • Storage: 5% to 95% non-condensing
Certifications	• CE      • FCC • CE LVD      • C-Tick
Dimensions	 <p>The image contains two technical drawings of the camera. The left drawing is a side profile view showing a height of 3.78" (96mm) and a width of 2.04" (52mm). The bottom edge has a width of 0.89" (23mm). The right drawing is a front view showing a width of 4.55" (116mm) and a height of 4.2" (107mm). The front view shows a lens in the center and two screws on either side.</p>
Warranty	
Warranty	5-Year Warranty <sup>2</sup>
Order Information	
Part Number	Description
DCS-6210	Full HD Mini Fixed Dome Network Camera

<sup>1</sup> Frame rates when streaming video may vary depending on network conditions and method used

<sup>2</sup> 5-Year Warranty available only in the USA

Updated 12/17/12

**U.S.A.** | 17595 Mt. Herrmann Street | Fountain Valley, CA 92708 | 800.326.1688 | dlink.com    **Canada** | 2525 Meadowvale Blvd | Mississauga, ON L5N 5S2 | 800.361.5265 | dlink.ca