

Veriton N

N4640G

Tiny form factor, lots of flexibility

- Tiny but expandable
- Flexible and adoptable
- Secure and manageable





























Veriton N4640G SPECIFICATIONS





Product views	 Microphone-in jack Headphone/speakers jack Three USB 3.0 ports One button recovery Power button 	6 DisplayPort™ 7 External display (VGA) port 8 USB 3.0 port 9 Two USB ports 10 Ethernet (RJ-45) port	 11 Audio combo port 12 DC-in jack for AC adapter 13 Additional Display Port
Operating system ^{1, 2}	Windows 10 Pro 64-bit Windows 10 Home 64-bit Windows 7 Professional 64-bit Service Pack 1		
CPU and chipset ¹	6 th Generation Intel [®] Core [™] i7 processors, Intel [®] HD Gra 6 th Generation Intel [®] Core [™] i5 processors, Intel [®] HD Gra 6 th Generation Intel [®] Core [™] i3 processors, Intel [®] HD Gra Intel [®] Pentium [®] processors, Intel [®] HD Graphics 510 Intel [®] Celeron [®] processors, Intel [®] HD Graphics 510 Chipset: Intel [®] H110 Express Chipset	aphics 530 aphics 530 aphics 530	
Memory ^{1, 3, 4}	8 GB / 4 GB DDR4 2133 MHz soDIMM Up to 16 GB of Dual-channel DDR4 2133 MHz		
Storage ^{1, 5}	Hard disk drive • 1 TB 2.5-inch 5400 RPM Solid State Hybrid Drive • 1 TB 2.5-inch 5400 RPM, 9.5 mm high • 500 GB 2.5-inch 5400 RPM Solid State Hybrid Drive • 500 GB 2.5-inch 5400 RPM • 256 GB / 128 GB / 60 GB M.2 2280 Solid State Drive		
Optical media drive	8X Super-Multi drive, 9.0 mm slim, tray-load		
Graphics ^{6 (Optional)}	NVIDIA [®] GeForce [®] GT 705, 1 GB DDR3	AMD Radeon [™] R7 340, 2 GB DDR3)	AMD Radeon [™] R5 310, 2 GB DDR3)
Audio	Integrated high-definition sound		
Communication	WLAN: 802.11ac/a/b/g/n wireless LAN and Bluetooth [®] 4 LAN: Gigabit Ethernet	.0 LE	
Expansion slots ¹	PCIe x16 slot(s): 1		
Software ⁷	Acer Office Manager CyberLink® PowerDVD® 12	Acer Control Center Office 2013	McAfee® Internet Security ProShield
Commercial features	USB cable HDMI [®] cable Intrusion alert (via BIOS) One-button recovery (OBR)	Kensington lock slot 100% solid capacitors DASH 1.1	Hard drive password protection (via BIOS) PXE (Preboot eXecution Environment) WOL (Wake On Lan)
Commercial selected options ⁸	VESA mounting kit Additional 2nd DisplayPort [™] TPM v1.2 (Trusted Platform Module)		
Dimensions	249.5 (W) x 204 (D) x 33.2 (H) mm (9.82 x 8.03 x 1.31 inches)		
Power supply and adapter	3-pin 135 W AC adapter 3-pin 90 W AC adapter		
System compliance	RoHS, DMI, GS, ENERGY STAR [®] , PC2001		
Options and accessories	Wireless (2.4 GHz RF) keyboard and mouse USB keyboard and mouse		
Certification	Citrix ready, BSMI, VCCI, CE, FCC, CB		

- Specifications vary depending on model.

 4-bit software is required to enjoy the advantages of 64-bit processing.

 A 64-bit operating system is required to enjoy the ultimate performance of 4 GB or higher memory.

 Memory speed may vary, depending on the CPU, chipset or memory fitted.

 1 GB is 1 billion bytes, 1 TB is 1000 GB. Actual formatted capacity is less and may vary depending on preloaded materials and operating environment. Recovery Management uses a portion of the stated hard disk capacity as dedicated backup space.
- Total available graphics memory comprises dedicated video memory, system memory, and shared system m This figure will vary depending on system memory, installed drivers, BIOS settings and other factors. Bundled software may vary depending on hardware configuration, OS and regional availability. Only one of the additional options can be selected.

In a continuing effort to improve the quality of our products, information in this document is subject to change without notice. Images shown are only representations of some of the configurations available for this model. Availability may vary depending on region.
© 2015. All rights reserved.
Microsoft and Windows are registered trademarks of Microsoft Corporation.
Intel, Intel Core, Core Inside, Pentium, and Pentium Inside are trademarks of Intel Corporation in the U.S. and other countries.

