

# **E2470SWHE**

**23.6** (59.9) LCD MONITOR

For work or home, this monitor offers excellent performance with 16.7 million colors and 5ms response time. Smart features like Eco Mode and e-Saver help you effortlessly reduce power consumption.

### **Screen Details**

| Resolution 1920x1080 PX  Refresh rate 60Hz  Response time 5  Panel TN  Backlight WLED  Aspect ratio 16:9  Brightness (typical) 250  Contrast (dynamic) 20M:1  Contrast (static) 1000:1  Pixel Pitch (H) (V) 0.2715  Diagonal (inch) 23.6  Active Screen Area (HxW) 521.28x293.32 mm  Viewing angle (CR10) 170/160 °  Display Colours 16.7 Million  OSD languages EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input VGA, HDMI 1.4 x 2  Audio output Headphone out (3,5mm) |                          |                                |
|--|--------------------------|--------------------------------|
| Refresh rate 60Hz  Response time 5  Panel TN  Backlight WLED  Aspect ratio 16:9  Brightness (typical) 250  Contrast (dynamic) 20M:1  Contrast (static) 1000:1  Pixel Pitch (H) (V) 0.2715  Diagonal (inch) 23.6  Active Screen Area (HxW) 521.28x293.32 mm  Viewing angle (CR10) 170/160   Display Colours 16.7 Million  OSD languages EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input VGA, HDMI 1.4 x 2   | Color                    | Black                          |
| Response time 5  Panel TN  Backlight WLED  Aspect ratio 16:9  Brightness (typical) 250  Contrast (dynamic) 20M:1  Contrast (static) 1000:1  Pixel Pitch (H) (V) 0.2715  Diagonal (inch) 23.6  Active Screen Area (HxW) 521.28x293.32 mm  Viewing angle (CR10) 170/160 °  Display Colours 16.7 Million  OSD languages EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input VGA, HDMI 1.4 x 2   | Resolution               | 1920x1080 PX                   |
| Panel TN  Backlight WLED  Aspect ratio 16:9  Brightness (typical) 250  Contrast (dynamic) 20M:1  Contrast (static) 1000:1  Pixel Pitch (H) (V) 0.2715  Diagonal (inch) 23.6  Active Screen Area (HxW) 521.28x293.32 mm  Viewing angle (CR10) 170/160 °  Display Colours 16.7 Million  OSD languages EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input VGA, HDMI 1.4 x 2  | Refresh rate             | 60Hz                           |
| Backlight WLED  Aspect ratio 16:9  Brightness (typical) 250  Contrast (dynamic) 20M:1  Contrast (static) 1000:1  Pixel Pitch (H) (V) 0.2715  Diagonal (inch) 23.6  Active Screen Area (HxW) 521.28x293.32 mm  Viewing angle (CR10) 170/160 °  Display Colours 16.7 Million  OSD languages EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input VGA, HDMI 1.4 x 2  | Response time            | 5                              |
| Aspect ratio 16:9  Brightness (typical) 250  Contrast (dynamic) 20M:1  Contrast (static) 1000:1  Pixel Pitch (H) (V) 0.2715  Diagonal (inch) 23.6  Active Screen Area (HxW) 521.28x293.32 mm  Viewing angle (CR10) 170/160 °  Display Colours 16.7 Million  OSD languages EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input VGA, HDMI 1.4 x 2  | Panel                    | TN                             |
| Brightness (typical) 250  Contrast (dynamic) 20M:1  Contrast (static) 1000:1  Pixel Pitch (H) (V) 0.2715  Diagonal (inch) 23.6  Active Screen Area (HxW) 521.28x293.32 mm  Viewing angle (CR10) 170/160 °  Display Colours 16.7 Million  OSD languages EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input VGA, HDMI 1.4 x 2   | Backlight                | WLED                           |
| Contrast (dynamic) 20M:1  Contrast (static) 1000:1  Pixel Pitch (H) (V) 0.2715  Diagonal (inch) 23.6  Active Screen Area (HxW) 521.28x293.32 mm  Viewing angle (CR10) 170/160 °  Display Colours 16.7 Million  OSD languages EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input VGA, HDMI 1.4 x 2   | Aspect ratio             | 16:9                           |
| Contrast (static) 1000:1  Pixel Pitch (H) (V) 0.2715  Diagonal (inch) 23.6  Active Screen Area (HxW) 521.28x293.32 mm  Viewing angle (CR10) 170/160 °  Display Colours 16.7 Million  OSD languages EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input VGA, HDMI 1.4 x 2   | Brightness (typical)     | 250                            |
| Pixel Pitch (H) (V)  Diagonal (inch)  23.6  Active Screen Area (HxW)  Viewing angle (CR10)  Display Colours  16.7 Million  OSD languages  EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input  VGA, HDMI 1.4 x 2   | Contrast (dynamic)       | 20M:1                          |
| Diagonal (inch)  23.6  Active Screen Area (HxW)  521.28x293.32 mm  Viewing angle (CR10)  170/160 º  Display Colours  16.7 Million  OSD languages  EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input  VGA, HDMI 1.4 x 2   | Contrast (static)        | 1000:1                         |
| Active Screen Area (HxW)  Viewing angle (CR10)  Display Colours  16.7 Million  OSD languages  EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input  VGA, HDMI 1.4 x 2   | Pixel Pitch (H) (V)      | 0.2715                         |
| Viewing angle (CR10)  Display Colours  16.7 Million  OSD languages  EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input  VGA, HDMI 1.4 x 2   | Diagonal (inch)          | 23.6                           |
| Display Colours  16.7 Million  OSD languages  EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input  VGA, HDMI 1.4 x 2   | Active Screen Area (HxW) | 521.28x293.32 mm               |
| OSD languages  EN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input  VGA, HDMI 1.4 x 2  | Viewing angle (CR10)     | 170/160 º                      |
| FI, PL, CZ, RU, KR, CN (T), CN (S), JP  Connections  Signal Input  VGA, HDMI 1.4 x 2   | Display Colours          | 16.7 Million                   |
| Signal Input VGA, HDMI 1.4 x 2   | OSD languages            | FI, PL ,CZ, RU, KR, CN (T), CN |
|  | Connections              |                                |
| Audio output Headphone out (3,5mm)   | Signal Input             | VGA, HDMI 1.4 x 2              |
|  | Audio output             | Headphone out (3,5mm)          |

| _  |    |    |      |     |
|----|----|----|------|-----|
| Fr | an | no | m    | ics |
|    | чν |    | ,,,, | 103 |

| Swivel         | 0 °      |
|----------------|----------|
| Tilt           | -5/+15 ° |
| Vesa Wallmount | 100x100  |

### **Power details**

| Powersupply       | Internal  |
|-------------------|---|
| Powersource       | 100 - 240V 50/60Hz                              |
| Power Consumption | On 17.96 watt, Off 0.19 watt Standby 0.37 watt, |

## **Dimensions**

| Product Dimensions (incl base) | 551.4x400.4x221 mm  |
|--------------------------------|---------------------|
| Product Dimensions (excl base) | 551.4x396.9x78.2 mm |
| CartonDimensions               | 620x435x127 mm      |
| Net Weight (excl package)      | 3.58                |
| Gross Weight (incl package)    | 5.21                |

# Warranty

| WarrantyPeriod | 3 Years       |
|----------------|---------------|
| EAN            | 4038986144193 |
| MTBF           | 50.000 hours  |

## What's in the box

VGA cable (1.2m m), HDMI cable (1.5m m), Power Cable C7 (1.2 m),

## Sustainability

- Environmental and energy: RoHS, Lead-free, Mercury Free
- $\bullet$  Recyclable packaging material: 100 %

## Regulations

TUV-GS, TUV-Bauart, CE, TCO 7, energystar, EPEAT No, FCC, EAC, Rohs compliant,