G2590PX



24.5 (62.2) LCD MONITOR





ЛОС

1ms Response Time

A pixel response time of 1ms GTG means speed without the smear for an enhanced experience. Fast-moving action and dramatic transitions will be rendered

smoothly without the effects of ghosting.



144Hz Refresh Rate

Equip yourself with twice the frame rate of other monitors and say goodbye to image stuttering and

blurry motion. With a 144Hz refresh rate every frame is rendered sharply and in smooth succession, so you can line up your shots accurately and appreciate high speed races in all their glory.



FreeSync

Whatever your setup, achieve the highest framerate and smoothest display possible via AMD Free-Sync Technology. Whether you're dashing through explosions or screeching around rain

slicked bends, wave goodbye to screen tearing and lag – and leave your opponents in your smoothly rendered dust.



Shadow Control

Bring the battle out of the shadows with Shadow Control! Brighten dark areas or sink them back into blackness on the fly, without affecting the rest of the display.

Screen Details

ColorBlackResolution1920x1080 PXRefresh rate144HzResponse time1PanelTNBacklightWLEDsRGB Coverage (%)96flickerfree~Aspect ratio16:9Brightness (typical)400Contrast (dynamic)50M:1Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)16.7 MillionAdobe RGB Coverage (%)84CSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN (S), JP		
Refresh rate144HzResponse time1PanelTNBacklightWLEDsRGB Coverage (%)96flickerfreeAspect ratio16:9Brightness (typical)400Contrast (dynamic)50M:1Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours84OSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	Color	Black
Response time1PanelTNBacklightWLEDsRGB Coverage (%)96flickerfreeAspect ratio16:9Brightness (typical)400Contrast (dynamic)50M:1Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours84OSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	Resolution	1920x1080 PX
PanelTNBacklightWLEDsRGB Coverage (%)96flickerfree•Aspect ratio16:9Brightness (typical)400Contrast (dynamic)50M:1Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)16.7 MillionAdobe RGB Coverage (%)84CSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	Refresh rate	144Hz
RateMBacklightWLEDsRGB Coverage (%)96flickerfreeAspect ratio16:9Brightness (typical)400Contrast (dynamic)50M:1Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	Response time	1
SRGB Coverage (%)96flickerfreeAspect ratio16:9Brightness (typical)400Contrast (dynamic)50M:1Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR , ES, PT, DE, IT, NL, SE, FI, PL , CZ, RU, KR, CN (T), CN	Panel	TN
flickerfreeAspect ratio16:9Brightness (typical)400Contrast (dynamic)50M:1Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	Backlight	WLED
Aspect ratio16:9Brightness (typical)400Contrast (dynamic)50M:1Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	sRGB Coverage (%)	96
Brightness (typical)400Contrast (dynamic)50M:1Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	flickerfree	1
Contrast (dynamic)50M:1Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR , ES, PT, DE, IT, NL, SE, FI, PL , CZ, RU, KR, CN (T), CN	Aspect ratio	16:9
Contrast (static)1000:1Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR , ES, PT, DE, IT, NL, SE, FI, PL , CZ, RU, KR, CN (T), CN	Brightness (typical)	400
Pixel Pitch (H) (V)0.2832Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	Contrast (dynamic)	50M:1
Diagonal (inch)24.5Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	Contrast (static)	1000:1
Active Screen Area (HxW)543.74x302.62 mmViewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR , ES, PT, DE, IT, NL, SE, FI, PL , CZ, RU, KR, CN (T), CN	Pixel Pitch (H) (V)	0.2832
Viewing angle (CR10)170/160 °Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR, ES, PT, DE, IT, NL, SE, FI, PL, CZ, RU, KR, CN (T), CN	Diagonal (inch)	24.5
Display Colours16.7 MillionAdobe RGB Coverage (%)84OSD languagesEN, FR , ES, PT, DE, IT, NL, SE, FI, PL ,CZ, RU, KR, CN (T), CN	Active Screen Area (HxW)	543.74x302.62 mm
Adobe RGB Coverage (%)84OSD languagesEN, FR , ES, PT, DE, IT, NL, SE, FI, PL ,CZ, RU, KR, CN (T), CN	Viewing angle (CR10)	170/160 º
OSD languages EN, FR , ES, PT, DE, IT, NL, SE, FI, PL ,CZ, RU, KR, CN (T), CN	Display Colours	16.7 Million
FI, PL ,CZ, RU, KR, CN (T), CN	Adobe RGB Coverage (%)	84
	OSD languages	FI, PL ,CZ, RU, KR, CN (T), CN

Connections

Signal Input	VGA, DisplayPort 1.2 x 1, HDMI 1.4 x 2
USB input	USB 3.0 x 4
Built-in Speakers	2 W x 2

What's in the box

 $\label{eq:VGA} \begin{array}{l} \text{VGA cable (1,8 m), HDMI cable (1,8 m), Displayport Cable (1,8 m), } \\ \text{Audio Cable (1,8 m), USB cable (1,8 m), Power Cable C7 (1.8 m), } \end{array}$

Sustainability

- Environmental and energy: RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

Pivot	1
Swivel	-45/45 °
Tilt	-3.5 / 19.5 °
Height Adjust Amount	130mm
Removable Stand	1
Vesa Wallmount	100x100
Power details	
Powersupply	Internal
Powersource	100 - 240V 50/60Hz
Power Consumption	On 28 watt, Off 0.5 watt Standby 0.5 watt,
Dimensions	
Product Dimensions (incl base)	558.6x199.5x513.2 mm
CartonDimensions	626x203x417 mm
Net Weight (excl package)	5.43
Gross Weight (incl package)	7.75
Warranty	
WarrantyPeriod	3 Years
EAN	4038986166096
MTBF	50.000 hours



