Hannsig

by **HANN**Spree

HP247HJB

60cm / 23.6" Diagonal White LED-Backlight







EU

- 1920 x 1080 WUXGA Resolution (60cm / 23.6" Diagonal)
- LED Backlight Monitor
- ULTRA-WIDE VIEWING ANGLE
- Full HD 1080P
- 80,000,000:1 Active Contrast
- 5ms Response Time
- VGA+DVI+HDMI Compatible Inputs
- Multi-Video Modes : PC / Movie / Game / ECO
- Built-In Stereo Speakers
- Tilt and Wall-Mountable (VESA)
- Low Power Consumption
- Multi-Functional Height Adjustable Stand
- Portrait Display





































HP247HJB | EU

60cm / 23.6" Diagonal White LED-Backlight

Har	nns.G
	HARMINICOKOO

by **HANN**Spree



	••••	
Physical	Kensington Lock	Yes
	VESA mounting	100 x 100mm
Controls	Front control	MENU ∧/☀️ V/順) ¡/ြ Ů
	On Screen Display	12 language: EN, TC, DE, FR, ES, IT, PT, NL, SC, JS, KR, Russian
	Preset Mode	PC, Movie, Game, ECO Modes
Container Loading	40' Standard	EU: 800
	20' Standard	EU: 400
Accessories	Power Cable(1.5m), VGA Cable(1.5m), Audio Cable(1.5m), User Manual (CD), Quick Start Guide (Paper)	
Color Plan	Black texture: back cover front bezel, arm, base	
Carton box	Brown carton	
Green product (Jan. 2009)	Yes	
Window 8	NA	
Others	PC99 function(must)	
Certification	CE, CB, GS ,TCO6.0, EnergyStar6.x	

Contact Information

Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local Hannspree authorized representatives for the availability of specific products in your area. Hannspree reserves the right to alter design and specifications as well as to change the accessories with equivalents without notice.

LCD Panel	Display size	60cm / 23.6" Diagonal White LED-Backlight
	Brightness	250cd/m2 (Typical)
	Contrast	1000:1 (Typical) 80,000,000:1 (Active Contrast)
	Pixel pitch	0.271(H) x 0.271(V)
	Resolution (H x V)	1920 x 1080
	Aspect Ratio	16:9
	Response time	5ms
	View angles LR,UD	H/V 178°/178°Ultra Wide Viewing Angle (IPS, ADS PLStype of panel)
	Color	WARM, NATURE, COOL, User Mode
	Panel surface	Anti-glare
	Display colors	16.7M Colors
PC Input Range	Horizontal Freq.	30 to 83KHz
	Vertical Freq.	56Hz to 75Hz
	Max. display frequency (Resolution H*V/Fv)	1920 x 1080 /60 Hz
Interface	Input	D-Sub x 1, HDMI x1,PC Audio x1 ,DVI-D (HDCP) x1
Output Terminal	Earphone	Yes
	Speaker	Yes
Power	Consumption	On: 28 W; Standby<=0.5W, Off<=0.5W
	AC Power Range	AC 100~240V, 50~60Hz
	Power Mode Indicator Light	Power on : Green (LED) Power saving : Amber(LED)
Operating Condition	Temperature	5°C ~ 35°C
	Humidity	20% ~ 85%, non-condensing
Physical	Dimension (W*D*H)	561 x 216 x 560mm
	Packing Dimension (W*D*H)	740 x 181 x 415mm
	Net weight	7.09Kg
	Gross weight	8.9Kg
	Tilt / Pivot / Swivel	-5° ~ 20° / 90° / -60°~60°