

## SC-22



A reliable and affordable 22” surveillance display with Full HD resolution and versatile video inputs ideal for security and control centre environments.

The SC-22 features an LED backlight 22” widescreen display with a full HD 1920 x 1080 resolution, delivering high picture clarity. Quick signal-switching and rapid response time guarantees surveillance efficiency. With Analogue, HDMI, and looping BNC I/O, the SC-22 is easily integrated into any security system. Auto NTSC/PAL detection and auto settings adjustment reduce maintenance effort. Coming with built-in speakers and stylish slim profile, the SC-22 is the ideal value display choice for security and surveillance environments.

- > FHD 1920 × 1080 resolution
- > Anti-Burn-in™ technology
- > Built-in Image Enhancer: 3D Comb Filter/Deinterlace/Noise Reduction
- > Versatile connectivity (BNC in/out, S-Video, VGA, HDMI, Audio in/out)
- > Looping BNC video inputs for multiple connections
- > Quick signal-switching time ( ≤ 0.8 sec. )
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount
- > Tilt capacity from -6° ~ 13°



# SC-22

## Specifications

## SC-22

<b>Panel</b>	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time	LED-Backlit TFT LCD 21.5" (546.86mm) FHD 1920 x 1080 0.248 mm 250 cd/m <sup>2</sup> (Typical) 1000:1 (Typical) 170°/160° (Typical) 16.7M 3 ms (GTG)
<b>Horizontal Resolution</b>	TV Lines	600TVL (NTSC), 600TVL (PAL)
<b>Frequency (H/V)</b>		H: 31.5 kHz - 80 kHz V: 50 Hz - 75 Hz
<b>Input</b>	Analogue HDMI CVBS S-Video	15-Pin D-Sub HDMI BNC x 1 4-Pin mini DIN
<b>Out</b>	CVBS	BNC x 1
<b>Audio</b>	Audio In Audio Out Speaker	3.5ø mm audio jack 3.5ø mm audio jack 1W x 2
<b>Power</b>	Power Supply Power Requirements Consumption	Internal 100 ~ 240V, 50 - 60Hz < 25 W (On) < 0.5 W (Off)
<b>Plug &amp; Play</b>	VESA	EDID
<b>Operating Conditions</b>	Temperature Humidity	0 °C ~ 40 °C 10% ~ 85%
<b>Storage Conditions</b>	Temperature Humidity	-20 °C ~ 60 °C 10% ~ 95%
<b>Mounting</b>	VESA FPMPMI	Yes (100 x 100mm)
<b>Tilt</b>	Tilt	-6° ~ 13°
<b>Dimensions</b>	Product (W x H x D) Packaging (W x H x D)	516.5 x 376 x 185mm (20.3" x 14.8" x 7.3") 565 x 420 x 116mm (22.2" x 16.5" x 4.6")
<b>Weight</b>	Product Weight Packaged Weight	3.4 kg (7.5 lbs) 4.5 kg (9.9 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	CB, FCC, CE, GOST-R, WEEE, RoHS
<b>Accessories</b>	Supplied	User manual, power cord, 15-Pin D-Sub cable, audio cable, warranty card



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping BNC video inputs allow multiple display connections



Video versatility, including VGA, HDMI, S-Video and BNC In/Out

