# 24" (23.6" viewable) Full HD 1080p Optical Touch Monitor



Intuitive Multi-Touch Design

**TD2420** 



The ViewSonic® TD2420 is the perfect solution for both commercial and consumer touch screen applications. With an intuitive multi-touch LED display, interactive stylus, and full HD resolution, the TD2420 delivers a versatile touch solution for use as a POS display, information kiosk, or in hospital and classroom environments. With Windows® 8 compatible Dual Point Optical technology, the TD2420 provides a fun and interactive experience to engage users. Equipped with 1920x1080 Full HD resolution, and 20,000,000:1 MEGA Dynamic Contrast Ratio, the ViewSonic TD2420 delivers extremely sharp and crisp images. As a complete multimedia package, the display also includes a pair of integrated 2-watt speakers with SRS Premium Sound®. HDMI, VGA, and DVI inputs provide flexible and convenient connectivity, while a VESA-mountable design offers additional convenience for use as a wall-mounted display. The versatile TD2420 is the one-stop solution for your multi-touch display needs.



# **Durable and Accurate Multi-touch Screen**

Simply touch, drag, resize, and manipulate photos, documents or web pages—just like on your favorite mobile devices! The included stylus provides additional interactivity to write, draw, and further explore your creativity. 7H scratch-resistant surface hardness ensures durability, as well as a consistent, high-quality touch experience.

# Full HD 1080p Display with 1920x1080 Resolution

The 24" (23.6" viewable) Full HD monitor supports image-intensive commercial applications, as well as image, gaming, and video applications for home entertainment. 20,000,000:1 MEGA Dynamic Contrast Ratio provides a crisp image with high-level details.





### . . . . . .

# Flexible Configuration Options with OptiSync® Digital/Analog Inputs

The TD2420 supports Windows® 7 and Windows® 8 touch functions and boasts USB HID (Human Interface Device) for plug-and-play. The TD2420 can be connected through USB for instant two-point touch operation and easy navigation. Multi-mode input technology supports HDMI, DVI and VGA signals for compatibility and configuration flexibility.

# 24" (23.6" viewable) Full HD 1080p Optical Touch Monitor



**TD2420** 



## **Eco-Mode Conserves More Energy**

ViewSonic's proprietary Eco-mode function is built into all LED displays, offering options to "Optimize (85%)" or "Conserve (80%)". Both modes reduce display brightness and conserve up to 20%\* energy. Especially in a low ambient light, Eco-mode adjusts brightness and improves visibility while reducing eye fatigue and prolonging the display's lamp life. With Ecomode, lamp replacement expenditures are reduced while practicing eco-friendliness.



# **ENERGY STAR® and EPEAT-Silver Certified**


The TD2420 is environmentally sound with an energy-saving LED backlight and Eco-mode options. Save up to 40%\* in energy costs when compared to a regular 24" monitor.



## Integrated Speakers with SRS Premium Sound®

The TD2420 monitor has two integrated speakers for enhanced multimedia performance with crystal clear stereo sound.





Specifications		
<b>LCD PANEL</b>	Type Display Area Optimum Resolution Brightness Contrast Ratio ynamic Contrast Ratio Viewing Angles Response Time Backlight Backlight Life Panel Surface	24" (23.6" viewable) Wide Color TFT Active Matrix LED 20.5" horizontal x 11.5" vertical; 23.6" diagonal 1920x1080 200 cd/m² (typ.) 1000:1 (typ.) 20,000,000:1 170° horizontal, 160° vertical 5ms (typ.) White-light LED 30,000 hours (min.) Anti-glare, hard-coating (7H)
VIDEO INPUT	Analog Digital Frequency Sync	RGB analog (0.7 / 1.0 Vp-p, 75 ohms) HDMI, DVI (TMDS, 100 ohms) Fh: 24~82kHz, Fv: 50~75Hz Separate Sync
AUDIO OUTPUT	Speakers	2-watt (x2)
COMPATIBILITY	PC Mac®	PC compatibles (Windows® 7 / 8 Operating System) n/a
CONNECTOR	Video Analog Video Digital Audio Power	15-pin mini D-sub (VGA) DVI-D (with HDCP) HDMI Audio In (3.5mm mini-jack) Headphone (3.5mm mini-jack) Internal power board, 3-pin plug (CEE22)
POWER	Voltage Consumption Optimize Conserve	AC 100–240V (universal), 50 / 60Hz 25W (typ.) 22W (typ.) 20W (typ.)
CONTROLS	Front Panel Buttons OSD	1, 2, Down, Up, Power Auto Image Adjust, Contrast/Brightness, Input Select, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall (See user guide for full OSD functionality)

ERGONOMICS	Tilt	20°~5°
OPERATING CONDITIONS	Temperature Humidity	32–104° F (0–40° C) 20–90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with Stand Physical without Stand Packaging	21.9 x 16.6 x 6.9 in. / 555.9 x 421.9 x 174.8 mm 21.9 x 13.7 x 2.2 in. / 555.9 x 346.8 x 56.1 mm 19.9 x 19.6 x 5.9 in. / 506 x 498 x 151 mm
WEIGHT	Net with Stand Net without Stand Gross	6.6 lb. / 3.0 kg 5.2 lb. / 2.4 kg 8.1 lb. / 3.7 kg
WALL MOUNT	VESA®	100mm x 100mm
REGULATIONS		CE,CB, BSMI, PSB, SASO, C-tick, e-standby, KC, UL/cUL, FCC-B (including ICES003), UL CoC, Mexico Energy, GOST-R/Hygienic, UkrSEPRO, TCO 5.2, Erp, CCC, China Energy, ENERGY STAR®, EPEAT Silver, WEEE, RoHS, SVHC list
RECYCLE / DISPOSAL		Please dispose of in accordance with local, state or federal laws.
POWER MANAGEMENT		ENERGY STAR® standards, EPEAT Silver
WARRANTY		Three-year limited warranty on parts, labor and backlight.

### What's in the box?

TD2420 display, power cable, audio cable, VGA cable, DVI cable, USB cable, stylus, Quick Start Guide, ViewSonic Wizard CD (available in some countries only)















\*Energy savings may vary based on actual usage and other factors. Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Premium Sound and the SRS Logo are trademarks or registered trademarks of SRS Labs. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16529-00B-02/13]