

Key **Features**

Seamless Viewing Experience | WQHD Resolution |
Loaded with Connectivity | Ultimate Color Accuracy
| Professional Color Processing Capability



Product **Description**

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2768 WQHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek frameless design, the VP2768 provides a near-seamless viewing experience ideal for multi-monitor setups. For simple, single-cable daisy chaining of multiple monitors, the VP2768 is equipped with future-proof DisplayPort technology, in addition to HDMI. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E≤2 value for superior color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Add to that 6-axis color adjustment functionality, and this monitor provides the ultimate color processing capability for professional applications. What's more, an advanced ergonomic design delivers customized comfort for increased productivity. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.

call: 888.881.8781Contact Salesemail: salesinfo@viewsonic.comvisit: viewsonic.com

Display:		Ergonomics:	
Display Size (in.):	27	Height Adjust (mm):	130
Viewable Area (in.):	27	Swivel:	120°
Type:	IPS	Pivot:	900
Resolution:	2560 x 1440	Tilt (Forward/Back):	-5° / 21°
Static Contrast Ratio:	1000:1	Weight (imperial):	
Dynamic Contrast Ratio:	20,000,000:1	Net (lbs):	15.17
Light Source:	WLED	Net Without Stand (lbs):	9.68
Brightness:	350 cd/m2	Gross (lbs):	21.16
Colors:	16.8M	Weight (metric):	
Color Space Support:	8-Bit	Net (kg):	6.88
Aspect Ratio:	16:9	Net Without Stand (kg):	4.39
Response Time (Typical GTG):	14ms	Gross (kg):	9.6
Viewing Angles:	178º horizontal, 178º vertical	Dimensions (imperial) (WxHxD):	
Backlight Life (Hours):	30,000	Packaging (in.):	28.3 x 10.6 x 18.1
Panel Surface:	Anti-glare, Hard coating (3H)	Physical (in.):	24.1 x 21.3 x 8.5
Compatibility:		Physical Without Stand (in.):	24.1 x 13.89 x 1.98
PC Resolution (max):	2560 x 1440	Dimensions (metric) (WxHxD):	
Connector:		Packaging (mm):	720 x 268 x 460
USB 3.0 Type A(4), USB 3.0 Type B(1), 3.5mm Audio Out(1), HDMI 1.4(2), Display Port(1), Display Port Out(1), Mini Display Port(1)		Physical (mm):	613 x 540.4 x 215
		Physical Without Stand (mm):	613 x 352.7 x 50.3
Power:		General:	
Consumption (typical):	35W	Regulations: CB ,CE, WEEE, RoHS, ErP, REACH,WHQL,HDMI1.4 compliance, cTUVus,FCC-B,Mexico CoC,EPEAT GOLD,Energy Star, Mexico Energy	
Consumption (max):	48W	PACKAGE CONTENTS: LCD Display, Power Cable (cable length :1.8M), DP	
Voltage:	AC 100-240V (universal), 50-60Hz	Cable (mini DP to DP) (cable length :1.8M), USB 3.0 UPstream Cable (Type B to A) (cable length :1.8M), Quick Start Guide, ViewSonic Wizard CD-ROM	
Stand-by:	0.3W	Recycle/Disposal: Please dispose of in accordance with local, state or	
Additional Hardware:		federal laws.	
Kensington Lock Slot: Controls:	1	Warranty: Three-year limited warranty on parts, labor and backlight	
Physical Controls:	1, 2, 3, 4, 5, Power	UPC: 766907893618	
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)		
Operating Conditions:			
Temperature:	32-104° F (0-40° C)		
Humidity (non-condensing):	20-90%		
Mount:			
VESA Compatible:	100 x 100 mm		

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (03/02/2017 01:35 PM PST)