

Multiple Video Input with Audio to HDMI Switcher - HDMI / VGA / Component

Product ID: VS721MULTI



The VS721MULTI Multiple Video Input to HDMI Switcher enables users to switch between 7 different audio-video sources to a single HDMI-equipped display.

This versatile switcher is the perfect solution for combining digital and analog video sources (RGB/YPbPr/YCbCr) with your digital HDMI display, eliminating the cost of upgrading individual components (i.e. DVD player, PC, VCR, etc.).

An all-in-one multimedia solution, the video converter/switcher includes support for full high definition 1080p video resolution as well as digital and analog audio. Plus, the switch features RS232 remote serial control, and includes a convenient IR remote control for switching between video sources .

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Convert analog and digital video to HDMI for a variety of applications such as switching between consumer electronics devices (e.g. Blu-ray Disc players, satellite receivers, video game consoles and other devices)

Features

- Supports analog PC Resolution input and output up to WUXGA (1920x1200) @ 60Hz
- HDMI and HDCP compliant
- Supports analog HDTV RGB/YPbPr/YCbCr input, output up to 1080p @ 60Hz

Hardware

| | |
|--------------------|--|
| Warranty | 2 Years |
| AV Input | HDMI S-Video Composite VGA Component |
| Ports | 7 |
| AV Output | HDMI |
| Cabling | HDMI |
| Audio | Yes |
| Industry Standards | High Speed HDMI, HDCP |

Performance

| | |
|-----------------------------|---|
| Maximum Analog Resolutions | VGA: 1920x1200, YPbPr: 1920x1080 |
| Maximum Digital Resolutions | 1920x1200 |
| Supported Resolutions | Support VGA mode, 640x480, 720x400, 800x600, 848x480, 1024x768, 1152x864, 1280x720, 1280x768, 1280x800, 1280x960, 1280x1024, 1360x768, 1400x1050, 1440x900, 1440x1050, 1600x1200, 1680x1050, 1920x1080, 1920x1200 Support YPbPR mode, 720x480, 720x576, 720x480, 720x576, 1280x720, 1920x1080, 1920x1080 |
| Wide Screen Supported | Yes |

Connector(s)

| | |
|-------------|--|
| Connector A | HDMI (19 pin) VGA (15 pin, High Density D-Sub) Component Video (3 x RCA) |
|-------------|--|



S-Video (4 pin, Mini-DIN)
Composite Video (1 x RCA)
RCA
3.5 mm Mini-Jack (3 Position)

Connector B HDMI (19 pin)

Software

OS Compatibility Windows 10 (32/64), 8/8.1 (32/64), 7 (32/64), Vista(32/64), XP(32/64), 2000
Windows Server 2008 R2, 2003(32/64)

Indicators

LED Indicators

- 1 - HDMI
- 2 - HDMI
- 3 - HDMI
- 4 - VGA
- 5 - YPbPr
- 6 - CVSB
- 7 - S-VIDEO

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Input Current 0.6 A

Output Voltage 12V DC

Output Current 1.5 A

Center Tip Polarity Positive

Plug Type M

Power Consumption (In Watts) 18



Environmental

| | |
|-----------------------|-----------------------------|
| Operating Temperature | 0c to 70c (32F to 158F) |
| Storage Temperature | -20c to 85c (-4F to 185F) |
| Humidity | 0% to 95% RH Non-Condensing |

Physical Characteristics

| | |
|-------------------|-------------------|
| Color | Black |
| Material | Aluminum |
| Product Length | 15.1 in [38.4 cm] |
| Product Width | 6.8 in [17.3 cm] |
| Product Height | 1.8 in [45 mm] |
| Weight of Product | 4.0 lb [1.8 kg] |

Packaging Information

| | |
|---------------------------|-------------------|
| Package Length | 18.1 in [45.9 cm] |
| Package Width | 10.2 in [26 cm] |
| Package Height | 3.5 in [90 mm] |
| Shipping (Package) Weight | 6.0 lb [2.7 kg] |

What's in the Box

| | |
|---------------------|--|
| Included in Package | multiple format to HDMI audio video switch |
| | IR remote control |
| | mounting kit |
| | RS232 serial cable (6 ft.) |
| | RS-232 control software CD |
| | universal power adapter (NA, EU, UK, AU) |
| | instruction manual |



****Product appearance and specifications are subject to change without notice.***

