# HOME GUARD

# **Digital Video Recorder**

### Data Sheet

A D1 digital video recorder (DVR) with HD output and pre-installed WD AV-GP hard drive. Features a clear, simple user interface and automatic setup (subject to your local ISP and router settings) for viewing live footage on your computer, tablet or smartphone, accessible from anywhere in the world. Records footage continuously for 25 – 400\* days from multiple CCTV cameras.

Installing this HomeGuard CCTV security digital video recorder could be the most effective step you ever take to secure your home or business. It will help to protect against criminal activity and actively deter criminals from targeting your property. HomeGuard CCTV can also provide vital evidence in the event of a crime being committed and protect you against litigation and false accusations. With the ability to view live footage through your smartphone, tablet or computer, this HomeGuard CCTV digital video recorder will offer you peace of mind, wherever you are in the world.



## How long will my DVR record for?\*

#### No. of Cameras Recording (Days)

	1	2	3	4	5	6	7	8
500GB	100	50	33	25	20	17	14	13
1ТВ	200	100	66	50	40	33	29	25
2TB	400	200	132	100	80	67	57	50

\* Representative times based on standard settings, actual recording times may vary. The DVR can be set to record over the oldest files to ensure uninterrupted recording, once the disk becomes full.

#### Contents

DVR Unit, DVR Power Adapter (UK and EU), Power Splitter Cable, Remote Control, Mouse and Instruction Manual.

Part Nos.	4 CH	8CH
500GB	65146	65149
1TB	65147	65150
2ТВ	65148	65151





## **CCTV Security Kits**

Data Sheet

CCIV	/ DVR Kits	Bullet Camera	Dome Cam	Dome Camera	
2 Camera Kit	4 Channel	x2			
2 + 2 Camera Kit	4 Channel	x2	x2	x2	
4 Camera Kit	4 or 8 Channel	x4			
4 + 4 Camera Kit	8 Channel	x4	x4	x4	
8 Camera Kit	8 Channel	x8			
OS: Embedded Linux Video/Audio input CVBS input: 4/8 channel BNC port (1.0Vp-p,75 Audio input: 4 channel RCA port Talk back : YES Video/Audio output CVBS output: 1 channel HD: Yes 1920 x 1080P, 1280 x 1024, 13	ohms), PAL/NTSC optional	Sensor: 1/3"CMOS Horizontal Resolution: 600TVL Minimum Illumination: 0.5Lux/OLux (IR Led on) Night Vision Range: 15-20m Signal System: PAL Scanning System: 2:1 Interlace S/N Ratio: 248dB AGC: Auto White Balance: Auto Exposure Mode: EE Gamma Correction: 0.45 IR LEDs: D5mm 24PCS	Sensor: 1/3"CMOS Horizontal Resolution Minimum Illumination 0.5Lux/OLux (IR Led on Night Vision Range: 11 Signal System: PAL Scanning System: 2:11 S/N Ratio: 248dB AGC: Auto White Balance: Auto Exposure Mode: EE Gamma Correction: 0. IR LEDs: D5mm 24PCS	n: 1) 5-20m nterlace	
1024 x 768, resolution option VGA: 1920 x 1080P, 1280 x 1024, 1 1024 x 768, resolution optio Audio output: 1 channel, RCA por Video/Audio Encode Real time surveillance resolution Video encode standard: H.264 Encode resolution: Main stream: Highest encode ability: 4 channel 2 channel Video frame rate: 1-25 fps/PAL,1 Encode control: Fixed code rate,w Video rate: 48Kbps-2048Kbps Stream type: Video audio hybrid Audio encode standard: G.711A	366 x 768, 1280 x 720, nal rt : D1 D1, CIF optional D1, CIF optional D1 (4CH) D1+ 6 channel CIF (8CH) -30 fps/NTSC ariable code rate optional stream/video stream	4 4 4 4 4 8 8 8 8 8	rt Nos. -CH 2 Camera 500GB Kit -CH 2+2 Camera 500GB Kit -CH 4 Camera 500GB Kit -CH 4 Camera 1TB Kit -CH 4 Camera 1TB Kit -CH 4+4 Camera 1TB Kit -CH 4+4 Camera 2TB Kit	65154 69129 65155 65156 65157 65158 65159 65160	
Audio rate: 64Kbps Dual stream: Yes Video play back: 4/8 channel pla Talk back: Two way audio talk bac Other Motion detection area: 396 squar HDD SATA port: 1x2T External Interface LAN port: 1 RJ45 10M/100M USB port: 2x USB2.0 in the rear+ 1 RS-485: 1 channel, half-duplex Electrical Specification Power supply: Input:100V-240V/5 Working temperature: -10° - +55° Working humidity: 10%90%	res (22 x 18) on each channel xUSB2.0 in the front 50/60hz Output:12V		-CH 8 Camera 2TB Kit	65161	