KPD677L

8CH H.264 DVR

USB Mouse Control with GUI Display



O FEATURES

USB Mouse Control with GUI OSD

• The GUI OSD interface is provided and used with your USB mouse.

> Intelligent Motion Trigger Recording

- Only the channel with an event will be recorded to effectively save a significant amount of hard disk space and have the maximized recording time.
- · Supports pre-alarm recording.

Remote Surveillance

- Mobile surveillance via our self-developed and free program, "EagleEyes", is supported on many popular mobile platforms, such as iPhone®, BlackBerry®, Windows® Mobile & Symbian.
- Network surveillance via the licensed software "Video Viewer", Internet Explorer, Mozilla Firefox or Google Chrome web browser, and QuickTime player is supported with up to 10 users' login simultaneously.

Remote Independent Operation

• Channel switching is independent from the local site, allowing users to have private image monitoring remotely.

> H.264 Video Compression Technology

- · Highly improves video quality for live, recording, and network.
- Recording file size is minimized for longest recording time.
- · Lower bit rate required for fastest network transfer.


Backup Function

• Supports USB flash drive and network backup.

> Audio / Video Support

- 4 audio-in, 1 audio-out to record sounds.
- Video output for LCD & CRT monitors simultaneously.

O REAR PANEL



O SPECIFICATIONS

Video Custom		NTCO / DAL /outs detection
Video System		NTSC / PAL (auto detection)
Video Compression Format		H.264
Video Input (Composite video signal 1 Vp-p 75 Ω BNC)		8 channels
Video Output (BNC)	lain Monitor	For stable display
C	all Monitor	For sequence display
Video Output (VGA)		Built-in VGA interface for LCD monitor
Audio Input / Output		4 audio inputs, 1 audio outputs (Mono)
Maximum Recording Rate	e Frame	704×480 pixels with 60 IPS <ntsc> / 704×576 pixels with 50 IPS <pal></pal></ntsc>
	CIF	352x240 pixels with 240 IPS <ntsc> / 352x288 pixels with 200 IPS <pal></pal></ntsc>
Image Quality Setting		BEST / HIGH / NORMAL
Hard Disk Storage		Accommodates 1 SATA HDD (Capacity up to 2TB)
Quick Search		Time / Motion / Alarm search mode
Recording Mode		Manual / Timer / Motion / Alarm / Remote
USB Mouse Control		YES
Motion Detection Area		16 × 12 grids per channel
Motion Detection Sensitivity		HIGH / NORMAL / LOW
Pre-alarm Recording		YES
Backup Device		USB 2.0 flash drive / Network
Web Transmitting Compression		
Format		H.264
Ethernet		10/100 Base-T. Supports remote control and live view via Ethernet
Web Interface		Licensed software "Video Viewer" / Internet Explorer, Mozilla Firefox or
		Google Chrome web browser / QuickTime player
		(10 users access simultaneously)
Natural Protects		*Operating System: Windows 7 / Vista / XP / 2000
Network Protocol		TCP/IP, PPPOE, DHCP and DDNS
Remote Independent Operation		YES
Remote Event Download & Playback		YES
Remote Live Audio		YES
Event Notification		By FTP & E-Mail
IR Remote Control		YES (IR receiver built-in)
Mobile Surveillance		YES
Picture Zoom		2X digital zoom
PTZ Control		YES
Alarm I/O		4 inputs, 1 output
Key Lock (Password Protection)		YES
User Level		Administrator & Operator
Video Loss Detection		YES
Camera Title		Supports up to 12 letters
Video Adjustable		Hue / Saturation / Contrast / Brightness
Date Display Format		YY/MM/DD, DD/MM/YY & MM/DD/YY
Daylight Saving		YES
Power Source (±10%)		DC 19V
Power Consumption (±10%)		< 42W
Operating Temperature		10℃ ~ 40℃ (50°F ~104°F)
Dimensions (mm)**		343(W) x 59(H) x 223(D)
System Recovery		System auto recovery after power failure
Optional Peripherals		Keyboard Controller

^{*}The specifications are subject to change without notice.
** Dimensional tolerance: ±5mm