

UTCC-DSIR

Fixed Lens Eyeball Camera



KEY FEATURES

- **CCD** 1/3"
- **Resolution** 800 TVL
- **Sensitivity Mono** 0.01 Lux (AGC On, IR Off) / 0 Lux with IR LED On)
- **Infra Red IR LEDs** 23
- **IR Range** 10 - 15m
- **Lens Size** 3.6mm Fixed
- **Voltage** 12V DC
- **Power Consumption** 100mA (275mA IR LED On)
- **Dimensions** H 99mm, Dia (base) 118mm
- **Weight** 433g

OTHER FEATURES

- Day Night
- Auto White Balance
- Auto Gain Control
- IP65
- 2-way adjustment
- Internal / External
- Weatherproof
- Pixelplus CMOS Technology
- No Complex OSD
- BNC Video Output
- Standard 12VDC Operation
- IR LED Models for Day/Night Operation
- True Day/Night ICR (ie LED Models)
- 960H Ready

MODEL	UTCC-DSIR
Power source	Regulated DC 12V
Power consumption	100mA (275mA IR LED On)
IR LED consumption	175mA 23pc Super Flux IR LED
Scanning system	2:1 Interface
Scanning frequency	15.734KHz(H), 59.95Hz(V)
Effective Pixels	976(H) x 582 (V)
Resolution	800 TVL
E-Shutter	PAL 1/25 - 15000s ; NTSC: 1/30 - 15000s
ACG/BLC	On
WB	AWB
Sync System	Internal
Min. Illumination	0 Lux IR LED On
Video output	1.0 Vp-p (75 ohm, composite)
S/N Ratio	more than 47dB (AGC OFF)
Video output	BNC Connector
Lens mount	Fixed mount
Lens	Fixed Lens models 3.6mm
Operating temperature	-10°C to +50°C / 14°F to 122°F
Operating humidity	Up to 90% (non-condensing)



Install a Balun within the base of the camera.

No need to order a separate base.

