

BRAVO Line IP Camera Series



TOP-301HMP - H.264 Megapixel IP Cube Camera

TOP-302HMP - H.264 Megapixel Wireless IP Cube Camera



FEATURES:

- H.264 / MPEG-4 / MJPEG Multi-Profile Streaming simultaneous
- Power over Ethernet (IEEE 802.3af) supported
- Megapixel Resolution at 1280 x 1024
- Wireless IEEE 802.11b/g built-in (TOP-302HMP)
- Built-in 6 pcs LED for night vision
- 4.2 mm Fixed Lens
- UPnP Auto port forwarding for easy setup
- Free 64CH Management Software
- Supports two way audio for users to transfer / receive audio over the IP network

SPECIFICATIONS

Pick-Up Device	1/4" Progressive Scan CMOS Sensor
Picture Elements	1280 x 1024 pixels
Minimum Illumination	1.0 Lux
Lens Type	4.2 mm Fixed Lens
CDS Sensor	Yes
Motion dection	10 zones
Video Compression	11 profiles simultaneously - H.264: SXGA, VGA, QVGA, QQVGA - MPEG4: VGA, QVGA, QQVGA - JPEG: SXGA, VGA, QVGA, QQVGA
Resolution	1280*1024 / 640*480 / 320*240 / 160*120
Image Frame rate	MegaPixel Mode : 15 FPS for 11 profiles VGA Mode : 30 fps for 9 profiles
Picture Adjustment	White Balance ; Color ; Brightness ; Contrast ; Sharpness ; Night Mode ; De-Noise;
Day & Night	6pcs LEDs
LED distance	10 meter
Audio Support	AMR (3GPP) / G.726 (32 Kbps) / G.711 (64 Kbps)
Audio Input / Output	Built-in Mic / Line Out
Wireless	802.11b/g/n (TOP-302HMP only)
WLAN encryption	WPA, WEP
Network	Ethernet (10/100 Base-T), RJ-45 Connector
Protocol	TCP, UDP, HTTP, SMTP, FTP, NTP, DNS, DDNS, DHCP, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, PPPoE, 3GPP, ICMP, Samba
UPnP	UPnP Discover, and UPnP Auto port forwarding
OS	Windows® 2000, XP, Vista
Browser	IE 6.0 or later / Firefox
Mobile Phone	3GPP mobile surveillance. Audio+video
Clients (simutaneously)	20
Power	DC 12V / PoE (IEEE 802.3af)
Power Consumption	5W
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	20% ~ 80% (non-condensing)
SDK	API / CGI documentation

